

	DOOR DESCRIPTION - LEGEND AA - HARDWARE: - MORTISE LOCK - "VINGCARD 1100" 1 1/2" EXCHINGES - SAVING EAR DOOR GUARD - ONEWAY VIEWER (1 REQ'D @ HANDICAPPED; LOWER VIEWER 40" AFF)
R.U. ENTRY DOOR	
R.U. CORR. DOOR	BB - HARDWARE: - SURFACE SLIDE BOLT HINGES - 1 1/2" PR. - SOUNDSEAL - PEMKO "SILICONE SEAL" DOOR GASKET APPLIED TO FRAME HEAD & JAMB - LATCHSET W/ OPERATING KNOB ROOM SIDE ONLY. NOTE: DEL. CARPET PAD UNDER DOOR FOR SILEG FIT TO RETARD SOUND TRAN.
ALUMIN.	CC - KAWNEER OR EQUAL NARROW STYLE (1/2" HG. POT. RAIL) W/ MFR'S STD. HARDWARE - 9/8" INSULATING TEMP GL., CRANKER PRAZE ALUM., FACTORY FINISH.

RICHARD MOLENAAR
ARCHITECT

SWAMINARYAN
HINDU
TEMPLE

JACKSON, MS.

DOOR NOTES

1. WOOD DOORS, HOLLOW METAL DOORS
TO BE 1 3/4" THK. UNLESS NOTED
OTHERWISE.
2. EXT. HOLLOW MET. DOORS TO OR FROM
CONDITIONED SPACE TO BE INSULATED.
3. WHERE REQ'D, DOOR HARDWARE
SHALL CONFORM TO APA &
GOVERNING HANDICAP CODE.
ALL HOL. MET. & WOOD DOORS TO
HAVE LEVER KNOBS.
4. WOOD & HOL. MET. DOORS THAT OPEN
AGAINST A WALL TO HAVE BUMPER
MOUNTED ON WALL WHEREVER POSSIBLE.
5. FURNISH HARDWARE UNDER AN
ALLOWANCE OF \$225 PER DOOR.

WALL KEYNOTES

- (1) E.I.F.S. ▲
- (2) 4" FACE BRICK
- (3) 1/2" GYP. BD.
- (4) GRAVITY AIR SPACE
- (5) ▲
- (6) 5/8" TYPE X GYP. BD.
- (7) 1/2" GYP. SHEATH.
- (8) 3/8" x 1/2" GA. (MIN.)
MET. STUDS, 16" O.C.
- (9) 3/8" x 2 1/2" GA. (MIN.)
MET. STUDS, 16" O.C.
- (10)
- (11)
- (12) 3/8" FIBERGL. INSUL.
BATT. (R-13) ▲
- (13)
- (14)

The image contains six hand-drawn architectural details of door thresholds and jamb connections, numbered 1 through 6.

- 1. THRESH. @ R.U. ENTRY:** A cross-section of a threshold for a right-hand unit (R.U.) entry. It shows a door frame with a door, a door shoe, and a door shoe gasket. The threshold is labeled "THRSH. @ R.U. ENTRY" and "OUTSIDE CORRIDOR ONLY".
- 2. THRESH. @ VEST.:** A cross-section of a threshold for a vestibule (VEST.) entry. It shows a door frame with a door, a door shoe, and a door shoe gasket. The threshold is labeled "THRSH. @ VEST.".
- 3. THRESH. @ INT. STUD WALL:** A cross-section of a threshold for an interior stud wall entry. It shows a door frame with a door, a door shoe, and a door shoe gasket. The threshold is labeled "THRSH. @ INT. STUD WALL".
- 4. JAMB @ INT. STUD WALL:** A cross-section of a jamb for an interior stud wall entry. It shows a door frame with a door, a door shoe, and a door shoe gasket. The jamb is labeled "JAMB @ INT. STUD WALL".
- 5. JAMB @ INT. STUD WALL:** A cross-section of a jamb for an interior stud wall entry. It shows a door frame with a door, a door shoe, and a door shoe gasket. The jamb is labeled "JAMB @ INT. STUD WALL".
- 6. JAMB @ INT. STUD WALL:** A cross-section of a jamb for an interior stud wall entry. It shows a door frame with a door, a door shoe, and a door shoe gasket. The jamb is labeled "JAMB @ INT. STUD WALL".

SCHEDULES

98002	A-4
4-3-96	