

3 medium


UNDER COUNTER
ELECT. WATER HTR.
W/ SAFE PAN W/DRAIN
EXTEND THRU OUTSIDE
WALL W/T & P RELIEF
PIPE TO SAFE PAN.
A.O. SMITH POINT OF
USE ELECT. WATER HTR.
MODEL NO. ELFS 15,
6 KW 208 V.

WATER HTR. MTD. ON STAND
W/ SAFE PAN. PIPE PAN
DRAIN TO FLR. DRAIN.
A.O. SMITH MODEL BT-30 TANK TYPE
GAS WATER HTR., 74.5 GAL., 75 MBH
NAT. GAS INPUT W/ FACTORY ASME
T & P RELIEF VALVE.

NOTE: PROVIDE 1/2" WATER CONN. EA.
FIXTURE, H & C, OR COLD ONLY AS REQ'D.
EXCEPT PROVIDE 3/4" C.W. CONN. @ URINALS.

PLUMBING FIXTURE SCHEDULE

- W-1 WATER CLOSET
- W-1H WATER CLOSET, HANDICAPPED
- L-1 LAVATORY
- L-1H LAVATORY, HANDICAPPED
- U-1 URINAL
- T-1 TUB/SHOWER
- T-1H TUB/HAND-HELD SHOWER, HANDICAPPED
- SH-1 SHOWER, PRE-FAB OR BUILT-IN
- S-1 KITCHEN SINK
- EDF ELECT. DRINKING FOUNTAIN (HI-LOW)



RICHARD MOLENAAR
ARCHITECT

SWAMINARAYAN
HINDU
TEMPLE
JACKSON, MS

SEE SHT. A-1 FOR FIRE RATED WALLS

FLOOR PLAN
PLUMBING-WATER 1/8" = 1'-0"

98001
4-3-98
M-3