

MISHRA

ARCHITECTURE PLLC

6800 S Creek Rd, Charlotte, NC 28277

Ph:(704) 625-6554 Fax:(704) 919-5822

EMÁIL:ashish@mishraarch.com

WEB: www.mishraarch.com

<u>CIVIL:</u> David Lane Beaird & Associates, Inc.

Email:fgadberry@dlbengineering.com

105 Commercial Parkway

11220 Elm Lane, Suite 201

Email: lwright@wgpminc.com

West Monroe, LA 71294

Phone: (318) 388-3227

STRUCTURAL: WGPM, Inc.

Charlotte, NC 28277 Phone: (704) 542-7199 Fax: (704) 542-7195

ELECTRICAL: Ritter Engineering 1043 Arroyo Vista Lane

Phone: (704) 516-0385

Email: shane@rittereng.com

MECHANICAL: Shultz Engineering Group, P.C.

212 North McDowell St., Suite 204

REVISIONS

Information contained on this drawing and

in all digital files associated is authorized

Description

Matthew, NC 28014

Fax: (704) 644-1464

Charlotte, NC 28204

Fax:(704) 347-0093

No. Date

Phone: (704) 334-7363

Email: don@shultzeg.com

6. LIGHTS IN THIS AREA MUST BE DAMP LOCATION RATED AND W/ SHATTER PROOF LENSES 7. WALL MOUNTED VANITY LIGHT - PROVIDE JUNCTION BOX, COORDINATED WITH FIXTURE 8. STARTING POINT OF TILE - BEGIN WITH FULL TILE 9. ALL ROOMS TO HAVE HSIA PER HILTON STANDARDS. IF HARD WIRED INTERNET ACCESS IS DESIRED, A RECEPTACLE MUST BE PLACED @ 34" A.F.F.

10. SHOWER / BATH DRAIN LOCATION 11. NO FINISHES UNDER SHOWER PAN / TUB 12. PROVIDE DEDICATED ELECTRICAL CIRCUIT FOR EACH UNDERCOUNTER APPLIANCE 13. DOORBELL ON/OFF SWITCH FOR COMMUNICATION FEATURE ROOMS ONLY - SIGNAGE AS REQUIRED 14. THRESHOLD - REFER TO STANDARDS MANUAL 15. SHOWER INDICATED: BATH TUBS MAY BE SUBSTITUTED - REFER TO STANDARDS 16. DASHED BOXES AND CIRCLES REPRESENT ACCESSIBLE

 HARDWIRED PACKAGED TERMINAL AIR CONDITIONER EXTERIOR WINDOW AND ASSOCIATED TREATMENTS 3. BARN DOOR ON EXPOSED HARDWARE - REFER TO DOOR SCHEDULE FOR MIRROR INSET APPLICATION 4. COMMUNICATING DOOR LOCATION WHEN USED 5. ARCHITECTURAL MILLWORK VALANCE PAINT TO MATCH GENERAL WALL COLOR - ANCHOR FROM CEILING

KEY NOTES:

CLEAR FLOOR AREAS - REFER TO ACCESSIBLE PLANS SHEET FOR ADDITIONAL INFORMATION 17. ACCESSIBLE DRAPERY CONTROL 18. DESK MUST PROVIDE MIN. 30" WIDE CLEAR FLOOR SPACE AND A MIN. 27" HIGH KNEE CLEARANCE 19. PROVIDE DRAIN IN THIS LOCATION IN GUEST BATHS EQUIPPED WITH ROLL-IN SHOWERS. DISH DRAIN AT A 6" RADIUS (1:48 SLOPE MAX). PROVIDE TRAP PRIMER 20. FLAT SCREEN TV TELEPHONE CENTER SCONCE ABOVE NIGHTSTAND 24. | EDGE OF PTAC SKIRT AT FLOOR

FURNISHING LEGEND: GF-100 ACTIVITY CHAIR

GF-101 OTTOMAN GF-102 SOFA SLEEPER GF-103 | SINGLE ARM SOFA SLEEPER GF-104 SINGLE ARM CHAISE GF-105 LOUNGE CHAIR GF-201 | GUESTROOM VANITY LIGHT GF-202 BEDSIDE TABLE LAMP AT NIGHTSTAND GF-203 SINGLE NIGHTSTAND SCONCE GF-204 DOUBLE NIGHTSTAND SCONCE GF-205 DESK LAMP GF-206 FLOOR LAMP GF-300 STREAMLINE UNIT GF-301 KING HEADBOARD GF-302 QUEEN HEADBOARD

GF-303 DOUBLE HEADBOARD GF-304 NIGHTSTAND GF-305 NIGHTSTAND WITH POWER GF-306 DOUBLE NIGHTSTAND WITH POWER GF-308 68" VANITY AT GUEST BATH GF-309 58" VANITY AT GUEST BATH GF-310 | ADA VANITY AT GUEST BATH GF-313 | STREAMLINE DIVIDER UNIT GF-314 | ADA STREAMLINE UNIT GF-315 | ADA STREAMLINE DIVIDER UNIT GF-318 42" VANITY AT GUEST BATH

GF-319 STREAMLINE DESK UNIT GF-400 WINDOW TREATMENT WITH PTAC GF-401 WINDOW TREATMENT WITHOUT PTAC GF-402 ROLLER SHADE GF-500 ARTWORK AT GUESTROOM GF-501 | ARTWORK AT GUEST BATH GF-502 ARTWORK AT SOFA IN SUITES GF-503 FRAMED MIRROR AT VANITY GF-504 FRAMED MIRROR AT DESK GF-505 FRAMED MIRROR AT ADA VANITY

GF-600 KING BED BASE GF-601 KING MATTRESS SET GF-602 KING BEDDING SET GF-603 ADAAG KING BED BASE GF-604 QUEEN BED BASE GF-605 QUEEN MATTRESS SET GF-606 QUEEN BEDDING SET GF-607 | ADAAG QUEEN BED BASE

FINISH LEGEND: B BASE C CARPET MIR MIRROR PT PAINT ST STONE SF SPECIAL FINISH T TILE

NOTE: REFER TO FF&E SPECIFICATIONS MANUAL AND COLOR AND MATERIAL SPECIFICATIONS MANUAL FOR FURNITURE ITEMS NOT VCT VINYL COMPOSITE TILE | IDENTIFIED WITHIN THESE WC WALL COVERING WD WOOD FINISH

for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express authorized individuals. Original drawing is 24"x36" and scales are as indicated. © 2013 MISHRA ARCHITECTURE PLLC

CEILING LEGEND: (X'-X" Y) CEILING HEIGHT

8'-6" C CEILING FINISH

A. PRIMED & PAINTED GYPSUM BOARD
PRIMED & PAINTED GYPSUM BOARD - MOISTURE
RESISTANT
C. UNDERSIDE OF FLOOR/ROOF SYSTEM - PRIMED AND
PAINTED - REFER TO STANDARDS

ELECTRICAL LEGEND: !ALERT! USUAL ALARMS TO BE FULLY VISIBLE GFI OUTLET FROM ALL AREAS TELEPHONE OUTLET

TV OUTLET SWITCH T REMOTE THERMOSTAT SD | SMOKE DETECTOR

STROBE (IN C.F. ROOMS ONLY) FIRE HORN/STROBE (IN C.F. ROOMS ONLY, OMIT FIRE HORNS WHEN THESE ARE USED) H | FIRE HORN (NON-C.F. ROOMS) SIDE WALL SPRINKLER HEAD D) DOORBELL LIGHT (C.F. ROOMS ONLY) HSIA (WIRED WHERE APPLICABLE) JUNCTION BOX

> EXHAUST FAN LIGHT AT CEILING

DOORBELL - MOUNT AT 46" AFF TO CENTER

OF BUTTON (C.F. ROOMS ONLY)

**KEY PLAN** 

Southern Hospitality Services

Hampton Inn and Suites

5400 I-20 & Frontage Rd.

Enlarged King Studio Plans

Monroe, LA 71201

CEILING LAYOUT LEGEND:

CENTER FIXTURE IN SPACE
- CENTER THE FIXTURE IN SPACE IDENTIFIED BY DIAGONAL LINE.

ALIGN FIXTURES
- ALIGN FIXTURES ALONG CENTERLINE SHOWN <u>CENTER OVER</u> - CENTER FIXTURE OVER CENTERLINE 工 ‡ 卫 OF ADJACENT CONSTRUCTION

GENERAL NOTES:

 WALLS BETWEEN ADJACENT ROOMS - ELECTRICAL OUTLET LOCATIONS, INCLUDING TV AND TELEPHONE OUTLETS, SHALL BE OFFSET 6" MIN. HORIZONTALLY -BACK TO BACK OUTLETS ARE NOT ALLOWED.
2. COMMUNICATION FEATURE ROOMS SHALL BE EQUIPPED WITH VISIBLE FIRE ALARMS AND COMMUNICATION FEATURE ROOM MUST HAVE A

VISIBLE NOTIFICATION DEVICE FOR THE TELEPHONE.

ACCESSIBLE ROOMS SHALL BE EQUIPPED WITH TOGGLE-TYPE SWITCHES.

Construction Documents

Elevations

12-111 Prepared by Author Checked by Checker

Released for PERMIT ONLY

Date Sept. 16, 2013