

10 A11 DOOR AT ELEVATORS SCALE: 1 1/2"=1'-0" SMOKE ACTIVATED HOLD OPEN DEVICE CONNECTED TO FIRE ALARM SYSTEM ASSEMBLY (4) NO MIN. FIRE DOOR ASSEMBLY (4) GYP. BD. (TYP.) WOOD FRAMING (TYP.) FACE OF FRAMED OPENING BELOW 2-HR. FIRE RATED WALL ELEVATOR Q OF ELEVATOR SHUTT ELEVATOR DOOR FRAME - INSTALL PER MANIF. RECOMMENDATIONS DOOR FRAME TO ELEV. JAMB 3/4" VERIFY W/DOOR MANIF. SMOKE ACTIVATED HOLD OPEN DEVICE CONNECTED TO FIRE ALARM SYSTEM ASSEMBLY (4) NO MIN. FIRE DOOR ASSEMBLY (4) 5 1/2" (2X6 STUD) 5 1/2" (2X6 STUD) 17'-0"		7a A11 ALUMINUM BULKHEAD SCALE: 3"=1'-0" DUAL-PANE INSULATED GLASS ALUM. BULKHEAD FOR DOOR TYPE REFER TO DOOR SCHED. (SHEET A9) FOR FIN. FL. REFER TO ROOM FIN. SCHED. (SHEET A9) FOR FLOORING TYPE REFER TO ROOM FIN. SCHED. (SHEET A9) BEVELED EDGE AFTER APPL. 1/8" REOTS. EXTR. ALUM. THRESHOLD - HIG. SET IN TILL BED OF SEALANT 1/4" 1/2"	
11 A11 RECESSED LIGHT FIXTURE FIRE PROTECTION DETAIL SCALE: 3"=1'-0" RECESSED LIGHT FIXTURE (WHERE OCCURS) FIRE-RESISTANT CEILING CONSTRUCTION (REFER TO SCHED. A10) SCALE: 3"=1'-0" FASTENER 5/8" TYPE 'X' GYPSUM BOARD (ALL SIDES) JOINT TAPE & COMPOUND ALL JOINTS NOTE: THIS DETAIL RECD ONLY WHERE RECESSED LIGHT CAN PENETRATES EXIST. CEILING DROPPED CEILING BELOW LATE ASSEMBLY. A10		7b A11 ALUMINUM THRESHOLD SCALE: 3"=1'-0" FOR DOOR TYPE REFER TO DOOR SCHED. (SHEET A9) FOR FIN. FL. REFER TO ROOM FIN. SCHED. (SHEET A9) METAL DOOR FRAME BEYOND FOR FINISH TYPE REFER TO ROOM FIN. SCHED. (SHEET A9) MARBLE THRESHOLD TO MATCH FRAME WIDTH 1/4" 1/2"	
12 A11 JAMB/INTERIOR SCALE: 3"=1'-0" WOOD STUDS - REFER TO PLAN FOR SIZE VARIES TYPICAL 5/8" GYP. BD. 2 1/4" METAL FRAME W/ ANCHORS AS RECD. VARIES		8 A11 BEARING WALL (BOTH WALLS) SCALE: 1 1/2"=1'-0" 2 X 6 BLOCKING WALL CONSTRUCTION DOOR BUMPER OVER FINISHED WALL NOTE: THIS DETAIL TYPICAL @ ALL INTERIOR DOORS & SIM. FOR ALL FIXTURES, ACCESSORIES, ETC.	
13 A11 JAMB/ INTERIOR (HEAD SIM.) SCALE: 3"=1'-0" 2 LAYER 5/8" TYPE 'X' GYPSUM BOARD EACH SIDE OF WALL METAL FRAME W/ ANCHORS AS RECD. SCALE: 3"=1'-0"		7c A11 MARBLE THRESHOLD SCALE: 3"=1'-0" 3/4" D.F. #1 STUDS @ 24" OC. 1ST FLOOR ONLY 2x4 D.F. #2 STUDS @ 24" OC. 2ND S&A & 4TH FLOORS SET STUDS ON INDEPENDANT 2x4 PT. D.F. PLATES 3" MINERAL WOOL BATT INSULATION 5/8" GYP. BD. (TYP.) 5/8" GYP. BD. (TYP.) 4" OC. NOTE: 2x4 STUDS IN BEARING WALL AT 2ND, 3RD & 4TH FLOORS MUST BE 1" DIA. ABOVE 2x4 STUDS AT 1ST FLOOR IMPORTANT NOTE	
14 A11 NOT USED		4 A11 JAMB/ INTERIOR SCALE: 3"=1'-0" CORRIDOR SIDE RESILL CHANNELS ON WALL PER 3/A10 5/8" GYP. BD. 1/2" GYP. BD. LAYER 2 1/4" METAL FRAME W/ ANCHORS AS RECD. VARIES 2X TRIMMER GUEST BATH 3 1/2" (2X4 STUDS)	
1 A11 JAMB/ EXTERIOR (HEAD SIM.) SCALE: 3"=1'-0" 5/8" GYP. BD. VARIES METAL FRAME W/ ANCHORS AS RECD. HEADER (REFER TO STRICT. PLAN) HEADER W/ ANCHORS AS RECD. CEMENT PLASTER O/ PLYWOOD		5 A11 JAMB/ INTERIOR SCALE: 3"=1'-0" CORRIDOR SIDE RESILL CHANNELS ON WALL PER 3/A10 5/8" GYP. BD. (TYP. X) 1/2" GYP. BD. (TYP. X) VARIES PREFINISHED STEEL DOOR FRAME METAL FRAME W/ ANCHORS AS RECD. GUEST ROOM SIDE NEXT NEAREST WALL STUD (WHERE OCCURS) 5/8" GYP. BD. (TYP. X) 5/8" GYP. BD. (TYP. X) HEADER (REFER TO STRICT. PLAN) WHERE OCCURS	
3 A11 JAMB/ INTERIOR (HEAD SIM.) SCALE: 3"=1'-0" 5/8" GYP. BD. VARIES METAL FRAME W/ ANCHORS AS RECD. HEADER (REFER TO STRICT. PLAN) HEADER W/ ANCHORS AS RECD. CEMENT PLASTER O/ PLYWOOD		2 A11 JAMB/ INTERIOR (HEAD SIM.) SCALE: 3"=1'-0" 5/8" GYP. BD. VARIES METAL FRAME W/ ANCHORS AS RECD. HEADER (REFER TO STRICT. PLAN) HEADER W/ ANCHORS AS RECD. CEMENT PLASTER O/ PLYWOOD	
6 A11 JAMB/ EXTERIOR (HEAD SIM.) SCALE: 3"=1'-0" 5/8" GYP. BD. VARIES METAL FRAME W/ ANCHORS AS RECD. HEADER (REFER TO STRICT. PLAN) HEADER W/ ANCHORS AS RECD. CEMENT PLASTER O/ PLYWOOD		8 A11 JAMB/ INTERIOR (HEAD SIM.) SCALE: 3"=1'-0" 5/8" GYP. BD. VARIES METAL FRAME W/ ANCHORS AS RECD. HEADER (REFER TO STRICT. PLAN) HEADER W/ ANCHORS AS RECD. CEMENT PLASTER O/ PLYWOOD	