

TELEPHONE SERVICE  
COORDINATE THE LOCATION OF ALL TELEPHONE SERVICE CONDUITS WITH THE  
LOCAL TELEPHONE COMPANY. PROVIDE SIZE AND QUANTITIES OF CONDUITS  
AS REQUIRED. PROVIDE CONDUITS FROM THE PBX ROOM TO A POINT AT THE  
PROPERTY LINE WITH CONDUITS STUBBED-UP AS DIRECTED BY THE LOCAL  
TELEPHONE COMPANY.

CATV SERVICE

COORDINATE THE LOCATION OF ALL CATV SERVICE CONDUITS WITH THE LOCAL CABLE TELEVISION COMPANY. PROVIDE SIZE AND QUANTITIES OF CONDUITS AS REQUIRED. PROVIDE CONDUITS FROM THE PBX ROOM TO A POINT AT THE PROPERTY LINE WITH CONDUITS STUBBED-UP AS DIRECTED BY THE LOCAL CABLE TELEVISION COMPANY.

ELECTRICAL SERVICE

1.) SERVICE VOLTAGE TO THIS PROJECT SHALL BE 120/208V, 3-PHASE, 4-WIRE, 60 HZ.

2.) THE ROUTING OF THE UNDERGROUND ELECTRIC PRIMARY SERVICE ENTRANCE SHALL BE AS DETERMINED BY THE LOCAL POWER COMPANY. PROVIDE NECESSARY UNDERGROUND CONDUITS CONSISTING OF THE SIZE AND QUANTITIES AS REQUIRED BY THE LOCAL POWER COMPANY.

3.) THE LOCATION OF THE PAD MOUNTED TRANSFORMER IS SHOWN ON THE ELECTRICAL SITE PLAN, HOWEVER THE PRECISE LOCATION SHALL BE COORDINATED WITH THE LOCAL POWER COMPANY.

4.) ARRANGE WITH THE LOCAL POWER COMPANY FOR BOTH TEMPORARY AND PERMANENT POWER TO THIS PROJECT. CONSULT WITH THE LOCAL POWER COMPANY REPRESENTATIVES TO INSURE THAT ADEQUATE POWER OF THE DESIRED VOLTAGE AND PHASE CHARACTERISTICS IS AVAILABLE. ASSIST THE OWNER IN OBTAINING THE NECESSARY SERVICE AGREEMENTS.

5.) ALL SERVICE REQUIREMENTS SHALL BE CAREFULLY INVESTIGATED BY AND COORDINATED BY THE ELECTRICAL CONTRACTOR. PROVIDE ALL REQUIRED FACILITIES INCLUDING, BUT NOT LIMITED TO:

TRENCHING AND BACKFILL, CONDUIT, PULL WIRES AND/OR ROPES & STRINGS, CABLE, CONNECTIONS, AND METERING PROVISIONS AND REQUIREMENTS.

6.) DO NOT BEGIN ANY WORK IN CONNECTION WITH THE MAIN SERVICE PRIOR TO RECEIVING AN ENGINEERING DRAWING FROM THE POWER COMPANY SHOWING THE REQUIRED FACILITIES.

1.) ALL WORK SHALL CONFORM TO ALL LOCAL, STATE AND NATIONAL ELECTRICAL CODES, INCLUDING THE LATEST EDITION OF THE N. E. C. AND ADA GUIDELINES.

2.) ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING AND PURCHASING ALL NECESSARY LICENSES, PERMITS, AND INSPECTIONS, AS WELL AS ANY OTHER FEES REGARDING THE ELECTRICAL INSTALLATION.

3.) CONNECT ALL PIV VALVES TO THE FIRE ALARM SYSTEM. -- VERIFY LOCATION OF ALL PIV VALVES WITH THE SPRINKLE CONTRACTOR.

4.) PAD MOUNTED TRANSFORMER BY LOCAL POWER COMPANY. PAD AS DIRECTED BY THE LOCAL POWER COMPANY.

5.) ALL WIRING SHOWN ON THIS SITE PLAN SHALL BE A MINIMUM OF #10 THHN / THWN COPPER IN A MINIMUM 3/4" C., UNLESS NOTED OTHERWISE.

6.) PROVIDE ALL NECESSARY DISCONNECT AND SWITCHES FOR ALL SIGNS -- COORDINATE ALL SIGN CONNECTIONS WITH SIGN CONTRACTOR.


7.) SEE SHEET "E405" FOR POLE BASE DETAIL.

8.) UNDERWATER POOL LIGHTS BY POOL CONTRACTOR.

9.) IN OUTDOOR STORAGE BUILDING PROVIDE 2-TYPE "H" FIXTURES WITH ZERO DEGREE BALLASTS CONTROLLED BY 1-S.P.S.T. SWITCH AND 1-GFI DUPLEX RECEPTACLE. ALL FEED FROM CIRCUITS "CC-16 & 18".



1 ELECTRICAL SITE PLAN  
1" = 20'-0"

ALL PARKING AREA FOOTCANDLE LEVELS SHALL BE 2 FC MAINTAINED. PARKING AREA LIGHTING ( TYPE "OG" & "OH" FIXTURES ) SHALL BE FURNISHED AND INSTALLED BY ELEC. CONTR. -- SUBMIT BOTH FIXTURES AND POLES TO "HOME2" FOR APPROVAL PRIOR TO PURCHASING.



DRAWING NOTES

A. PLEASE REFER TO SHEET E000 FOR PROJECT NOTES, LEGEND  
SCHEDULES, & DETAILS



M I S H R A  
ARCHITECTURE PLLC

6800 S Creek Rd, Charlotte, NC 28277  
Ph:(704) 625-6554 Fax:(704) 919-5822  
EMAIL:ashish@mishraarch.com  
WEB: www.mishraarch.com

**CIVIL:**  
Benchmark Engineering and Surveying  
101 Highpointe Court, Suite B  
Brandon, MS 39042  
Phone: (601) 591-1077  
Fax: (601) 591-0177  
Email:mikebes@bellsouth.net

**STRUCTURAL:**  
Whisonant Engineering Services, LLC  
122 Nut Tree Court  
Lexington, SC 29074  
Phone: (803) 957-4008  
Email: bill@weslex.com

**MEP:**  
Innovative Engineering Services, LLC  
2787 Stage Center DR., Suite 101  
Bartlett, TN 38134  
Phone: (901) 379-0500  
Email: [rhertter@innovativees-llc.com](mailto:rhertter@innovativees-llc.com)

[illegible]

Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated.<sup>B</sup>  
2011 MISHRA ARCHITECTURE PLLC



### KEY PLAN

Pramukh Vicksburg.  
LLC

HOME2suites  
Vicksburg

Berryman Road  
Vicksburg, MS 39180

Drawing Title

**ELECTRICAL - SITE PLAN**

Phase  
Construction Document

|             |          |
|-------------|----------|
| Project No. | 19005    |
| Prepared by | PTH      |
| Checked by  | RJH      |
| Date        | 04/02/19 |

Sheet No. E10

Released for

HOME2suires Vicksburg



[illegible]

Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated.<sup>9</sup>  
2011 MISHRA ARCHITECTURE PLLC



### KEY PLAN

Pramukh Vicksburg.  
LLC

HOME2suits  
Vicksburg

Berryman Road  
Vicksburg, MS 39180

Drawing Title


ELECTRICAL - SITE  
PHOTOMETRICS

---

Phase  
Construction Documents

|             |          |
|-------------|----------|
| Project No. | 19005    |
| Prepared by | PTH      |
| Checked by  | RJH      |
| Date        | 04/02/19 |

Released for



| OUTDOOR LIGHT FIXTURE SCHEDULE |          |                                                   |                                          |                                                                                                                          |                                            |                 |                   |         |
|--------------------------------|----------|---------------------------------------------------|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|-----------------|-------------------|---------|
| Label                          | Quantity | Manufacturer                                      | Catalog Number                           | Description                                                                                                              | Lamp                                       | Lumens Per Lamp | Light Loss Factor | Wattage |
| OA                             | 8        | Hydrel                                            | TPS1 18LED<br>WHT41K MFL FCL             | AXIAL LED FLOODLIGHT 8.4" OD X<br>10.5" LONG                                                                             | 18 CHIP LED<br>ARRAY                       | 2581            | 1                 | 34      |
| OB                             | 7        | BEGA Converted<br>by LUMGaTV<br>08.09.2017 / H.R. |                                          | 33 308 K3                                                                                                                | LED 2.1W                                   | 66              | 1                 | 3       |
| OF                             | 2        | Hydrel                                            | M9700 22LED<br>WHT53K MFL                | M9700 LAMP MODULE. 9"DIA. X<br>3"DEPTH WITH 18 WHITE 53K LED<br>WITH MFL OPTICS. TEMPERED CLEAR<br>FLAT LENS. TEMP 53.2C | ONE 20.5-<br>WATT LED,<br>AIMED UP<br>POS. | Absolute        | 1                 | 20.5    |
| OG                             | 14       | Lithonia Lighting                                 | DSX1 LED 60C<br>1000 40K T4M<br>MVOLT HS | DSX1 LED with 60 LEDs @ 1000 mA ,<br>4000K , TYPE 4 MEDIUM OPTICS<br>WITH HOUSE-SIDE SHIELD                              | LED                                        | 17084           | 1                 | 209     |
| OH                             | 0        | Lithonia Lighting                                 | DSX1 LED 60C<br>1000 40K T4M<br>MVOLT HS | DSX1 LED with 60 LEDs @ 1000 mA ,<br>4000K , TYPE 4 MEDIUM OPTICS<br>WITH HOUSE-SIDE SHIELD                              | LED                                        | 17084           | 1                 | 418     |
| OL                             | 0        | Lithonia Lighting                                 | DSF2 LED 4<br>A530/40K HMF<br>MVOLT      | D-SERIES FLOOD SIZE 2 WITH 4<br>COB, 4000K, (HMF) DISTRIBUTION,<br>NEMA TYPE 6HX4V                                       | LED                                        | Absolute        | 1                 | 79.35   |
| OK                             | 4        | Lithonia Lighting                                 | DSXW1 LED 20C<br>700 40K T4M<br>MVOLT    | DSXW1 LED WITH 2 LIGHT ENGINES,<br>20 LED'S, 700mA DRIVER, 4000K<br>LED, TYPE 4 MEDIUM OPTIC                             | LED                                        | 4430            | 1                 | 47      |

| Statistics  |        |        |         |        |         |         |
|-------------|--------|--------|---------|--------|---------|---------|
| Description | Symbol | Avg    | Max     | Min    | Max/Min | Avg/Min |
| SITE PLAN   | +      | 2.8 fc | 19.3 fc | 0.0 fc | N/A     | N/A     |
| POOL PLAN   | +      | 5.5 fc | 25.2 fc | 0.7 fc | 36.0:1  | 7.9:1   |



**POOL EQUIPMENT:**

ELECTRICAL CONTRACTOR SHALL VERIFY EXACT LOCATIONS & ELECTRICAL REQUIREMENTS OF ALL POOL EQUIPMENT INCLUDING, BUT NOT LIMITED TO: POOL PUMP OR PUMPS, SPA PUMP OR PUMPS, UNDERWATER POOL LIGHTS, TRANSFORMERS, DEHUMIDIFIERS, CONDENSING UNITS, ETC. PRIOR TO THE ROUGH-IN OF ANY ELECTRICAL EQUIPMENT. ELECTRICAL CONTRACTOR SHALL NOTIFY THE OWNER & ARCHITECT OF ANY CONFLICTS WITH THE ELECTRICAL DESIGN DRAWINGS AND THE EQUIPMENT FURNISHED BY THE OWNER AND THE POOL CONTRACTOR. ALL POOL AREA LIGHTING, EQUIPMENT, AND RECEPTACLE CIRCUITS SHALL HAVE GFCI PROTECTION.


**LAUNDRY EQUIPMENT:**

ELECTRICAL CONTRACTOR SHALL VERIFY EXACT LOCATIONS & ELECTRICAL REQUIREMENTS OF ALL LAUNDRY EQUIPMENT INCLUDING, BUT NOT LIMITED TO:

COMMERCIAL WASHERS & DRYERS, GUEST WASHERS & DRYERS, WATER SOFTENERS, MOTORIZED LOUVERS, SOAP DISPENSERS, ETC. PRIOR TO THE ROUGH-IN OF ANY ELECTRICAL EQUIPMENT. ELECTRICAL CONTRACTOR SHALL NOTIFY THE OWNER & ARCHITECT OF ANY CONFLICTS WITH THE ELECTRICAL DESIGN DRAWINGS AND OWNER SUPPLIED EQUIPMENT.



**INNOVATIVE • ENGINEERING**  
SERVICES, LLC



**MISHRA**  
ARCHITECTURE PLLC

6800 S Creek Rd, Charlotte, NC 28277  
Ph: (704) 625-6554 Fax: (704) 919-5822  
EMAIL: ashish@mishraarch.com  
WEB: www.mishraarch.com

**CIVIL:**  
Benchmark Engineering and Surveying  
101 Highpointe Court, Suite B  
Brandon, MS 39042  
Phone: (601) 591-1077  
Fax: (601) 591-0177  
Email: mikebes@bellsouth.net

**STRUCTURAL:**  
Whisonant Engineering Services, LLC  
122 Nut Tree Court  
Lexington, SC 29074  
Phone: (803) 957-4008  
Email: bill@weslex.com

**MEP:**  
Innovative Engineering Services, LLC  
2787 Stage Center DR., Suite 101  
Bartlett, TN 38134  
Phone: (901) 379-0500  
Email: rhtetter@innovativees-llc.com

| REVISIONS |          |                 |
|-----------|----------|-----------------|
| No.       | Date     | Description     |
| 1         | 04/22/19 | Owner Request   |
| 2         | 05/06/19 | Hilton Comments |
| 3         | 05/21/19 | Added PBX       |
|           |          |                 |
|           |          |                 |
|           |          |                 |
|           |          |                 |
|           |          |                 |
|           |          |                 |
|           |          |                 |
|           |          |                 |

Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated. 2011 MISHRA ARCHITECTURE PLLC



**KEY PLAN**

Pramukh Vicksburg, LLC

HOME2suites  
Vicksburg

Berryman Road  
Vicksburg, MS 39180

Drawing Title


**ELECTRICAL - FIRST  
FLOOR POWER PLAN**

Phase  
Construction Documents

Project No. 19005  
Prepared by PTH  
Checked by RJH  
Date 04/02/19

Sheet No.  
**E201**

Released for



① FIRST FLOOR PLAN - POWER  
1/8" = 1'-0"


**GENERAL MECHANICAL EQUIPMENT WIRING NOTES:**

1. PROVIDE RECESSED J-BOX AND CONDUIT TO CEILING FOR THERMOSTATS AS REQUIRED BY MECHANICAL TRADES.
2. SEE PANELBOARD SCHEDULES FOR CIRCUIT NUMBER INFORMATION.
3. PROVIDE DISCONNECTS AS SHOWN IN SCHEDULE WITH FLEXIBLE CONNECTION TO VIBRATING EQUIPMENT. MOUNT DISCONNECT ADJACENT TO EQUIPMENT.
4. WHILE THE EQUIPMENT SHOWN IS BELIEVED TO BE ACCURATE, VERIFY WIRING AND OVERCURRENT PROTECTION REQUIREMENT AS INDICATED BY NAMEPLATE ON ACTUAL EQUIPMENT INSTALLED. DO NOT CIRCUIT EQUIPMENT UNTIL VERIFICATION IS MADE, THEN CIRCUIT ACCORDINGLY. PROVIDE NEMA 3R DISCONNECTS FOR ALL OUTSIDE UNITS.



GENERAL NOTES THIS SHEET:


1. INCREASE THE WIRE SIZE A MINIMUM OF ONE SIZE ON ALL 120V. HOME-RUNS OVER 100 FEET IN LENGTH. INCREASE THE WIRE SIZE A MINIMUM OF ONE SIZE FOR ALL 208V. HOME-RUNS OVER 150 FEET IN LENGTH.
2. VERIFY THE ELECTRICAL REQUIREMENTS OF ALL MECHANICAL EQUIPMENT WITH THE MECHANICAL CONTRACTOR AND HIS SUPPLIER PRIOR TO ROUGH-IN.
3. EMERGENCY LIGHTS IN CORRIDOR SHALL BE WIRED ON A SINGLE CIRCUIT PER FLOOR.
4. WHERE EXIT SIGNS ARE MOUNTED FROM THE CEILING, THERE SHALL ALSO BE LOW LEVEL EXIT SIGNS. THE BOTTOM OF THE SIGN SHALL BE NOT LESS THAN 10" & NO MORE THAN 12" ABOVE THE FLOOR LEVEL. THE SIGN SHALL BE FLUSH MOUNTED TO THE DOOR OR WALL. WHERE MOUNTED ON THE WALL, THE EDGE OF THE SIGN SHALL BE WITHIN 4" OF THE DOOR FRAME ON THE LATCH SIDE.



1 FIRST FLOOR PLAN - LIGHTING  
1/8" = 1'-0"

| REVISIONS |          |               |
|-----------|----------|---------------|
| No.       | Date     | Description   |
| 1         | 04/22/19 | Owner Request |
| 4         | 07/16/19 | Code Response |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |

Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated. 2011 MISHRA ARCHITECTURE PLLC



KEY PLAN

Pramukh Vicksburg.  
LLC

HOME2suits  
Vicksburg

Berryman Road  
Vicksburg, MS 39180

Drawing Title  
ELECTRICAL - FIRST  
FLOOR LIGHTING PLAN

Phase  
Construction Documents

Project No. 19005  
Prepared by PTH  
Checked by RJH  
Date 04/02/19

Sheet No.  
E202


Released for



Released for

HOME2suits Vicksburg

1. INCREASE THE WIRE SIZE A MINIMUM OF ONE SIZE ON ALL 120V. HOME-RUNS OVER 100 FEET IN LENGTH. INCREASE THE WIRE SIZE A MINIMUM OF ONE SIZE FOR ALL 208V. HOME-RUNS OVER 150 FEET IN LENGTH.
2. VERIFY THE ELECTRICAL REQUIREMENTS OF ALL MECHANICAL EQUIPMENT WITH THE MECHANICAL CONTRACTOR AND HIS SUPPLIER PRIOR TO ROUGH-IN.
3. EMERGENCY LIGHTS IN CORRIDOR SHALL BE WIRED ON A SINGLE CIRCUIT PER FLOOR.
4. WHERE EXIT SIGNS ARE MOUNTED FROM THE CEILING, THERE SHALL ALSO BE LOW LEVEL EXIT SIGNS. THE BOTTOM OF THE SIGN SHALL BE NOT LESS THAN 10" & NO MORE THAN 12" ABOVE THE FLOOR LEVEL. THE SIGN SHALL BE FLUSH MOUNTED TO THE DOOR OR WALL. WHERE MOUNTED ON THE WALL, THE EDGE OF THE SIGN SHALL BE WITHIN 4" OF THE DOOR FRAME ON THE LATCH SIDE.






RYAN J. HEATTER  
ENGINEER  
LICENSED PROFESSIONAL  
19912  
STATE OF MISSISSIPPI  
4/2/19

HOME2suites  
Vicksburg

---

HOME2suites Vicksburg

1. INCREASE THE WIRE SIZE A MINIMUM OF ONE SIZE ON ALL 120V. HOME-RUNS OVER 100 FEET IN LENGTH. INCREASE THE WIRE SIZE A MINIMUM OF ONE SIZE FOR ALL 208V. HOME-RUNS OVER 150 FEET IN LENGTH.
2. VERIFY THE ELECTRICAL REQUIREMENTS OF ALL MECHANICAL EQUIPMENT WITH THE MECHANICAL CONTRACTOR AND HIS SUPPLIER PRIOR TO ROUGH-IN.
3. EMERGENCY LIGHTS IN CORRIDOR SHALL BE WIRED ON A SINGLE CIRCUIT PER FLOOR.
4. WHERE EXIT SIGNS ARE MOUNTED FROM THE CEILING, THERE SHALL ALSO BE LOW LEVEL EXIT SIGNS. THE BOTTOM OF THE SIGN SHALL BE NOT LESS THAN 10" & NO MORE THAN 12" ABOVE THE FLOOR LEVEL. THE SIGN SHALL BE FLUSH MOUNTED TO THE FLOOR OR WALL. WHERE MOUNTED ON THE WALL, THE EDGE OF THE SIGN SHALL BE WITHIN 4" OF THE DOOR FRAME ON THE LATCH SIDE.



① THIRD FLOOR PLAN  
1/8" = 1'-0"




**STRUCTURAL:**  
Whisonant Engineering Services, LLC  
122 Nut Tree Court  
Lexington, SC 29074  
Phone: (803) 957-4008  
Email: bill@weslex.com

**MEP:**  
Innovative Engineering Services, LLC  
2787 Stage Center DR., Suite 101  
Bartlett, TN 38134  
Phone: (901) 379-0500  
Email: [rhertter@innovativees-llc.com](mailto:rhertter@innovativees-llc.com)

[illegible]

Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated.<sup>2</sup>  
2011 MISHRA ARCHITECTURE PLLC



## KEY PLAN

Pramukh Vicksburg.  
LLC

HOME2suits  
Vicksburg

Berryman Road  
Vicksburg, MS 39180


Drawing Title

ELECTRICAL - FOURTH  
FLOOR PLANPhase  
Construction Documents

|             |          |
|-------------|----------|
| Project No. | 19005    |
| Prepared by | PTH      |
| Checked by  | RJH      |
| Date        | 04/02/19 |

Released for

1. INCREASE THE WIRE SIZE A MINIMUM OF ONE SIZE ON ALL 120V. HOME-RUNS OVER 100 FEET IN LENGTH. INCREASE THE WIRE SIZE A MINIMUM OF ONE SIZE FOR ALL 208V. HOME-RUNS OVER 150 FEET IN LENGTH.
2. VERIFY THE ELECTRICAL REQUIREMENTS OF ALL MECHANICAL EQUIPMENT WITH THE MECHANICAL CONTRACTOR AND HIS SUPPLIER PRIOR TO ROUGH-IN.
3. EMERGENCY LIGHTS IN CORRIDOR SHALL BE WIRED ON A SINGLE CIRCUIT PER FLOOR.
4. WHERE EXIT SIGNS ARE MOUNTED FROM THE CEILING, THERE SHALL ALSO BE LOW LEVEL EXIT SIGNS. THE BOTTOM OF THE SIGN SHALL BE NOT LESS THAN 10" & NO MORE THAN 12" ABOVE THE FLOOR LEVEL. THE SIGN SHALL BE FLUSH MOUNTED TO THE DOOR OR WALL. WHERE MOUNTED ON THE WALL, THE EDGE OF THE SIGN SHALL BE WITHIN 4" OF THE DOOR FRAME ON THE LATCH SIDE.




① FOURTH FLOOR PLAN  
1/8" = 1'-0"



A circular professional engineer seal for the State of Mississippi. The outer ring contains the text "RYAN J. HERTTER" at the top and "STATE OF MISSISSIPPI" at the bottom. Inside the ring, the text "LICENSED PROFESSIONAL ENGINEER" is written in a semi-circle. In the center, the license number "19912" is printed. A handwritten signature, "Ryan J. Hertter", is written across the seal. To the right of the seal, the date "5/21/19" is handwritten.

Released for

ANY COMPONENTS OR METHODS FOUND NOT IN COMPLIANCE WITH THIS SPECIFICATION SHALL BE REPAIRED OR REPLACED AT THE SATISFACTION OF THE OWNER'S REPRESENTATIVE BEFORE SUBMITTAL OF THE L.P.I. INSPECTION REPORT AND DELIVERY OF THE L.P.I. CERTIFIED SYSTEM LABEL.



HOME2suites Vicksburg



| REVISIONS |          |               |
|-----------|----------|---------------|
| No.       | Date     | Description   |
| 4         | 07/16/19 | Code Response |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |

Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated. 2011 MISHRA ARCHITECTURE PLLC



KEY PLAN

Pramukh Vicksburg, LLC

HOME2suites  
Vicksburg


Berryman Road  
Vicksburg, MS 39180

Drawing Title  
ELECTRICAL TYPICAL  
ROOM ENLARGED


Phase  
Construction Documents

|             |          |           |      |
|-------------|----------|-----------|------|
| Project No. | 19005    | Sheet No. | E301 |
| Prepared by | PTH      |           |      |
| Checked by  | RJH      |           |      |
| Date        | 04/02/19 |           |      |


Released for




1 KING STUDIO  
1/4" = 1'-0"




2 KING ONE BEDROOM  
1/4" = 1'-0"




3 DOUBLE QUEEN STUDIO  
1/4" = 1'-0"




4 ACCESSIBLE KING ROLLIN STUDIO  
1/4" = 1'-0"




5 ACCESSIBLE QUEEN STUDIO  
1/4" = 1'-0"




6 ACCESSIBLE KING ONE BEDROOM  
1/4" = 1'-0"



7 HEARING IMPAIRED KING STUDIO  
1/4" = 1'-0"



8 HEARING IMPAIRED KING ONE  
BEDROOM (HI)  
1/4" = 1'-0"



9 HEARING IMPAIRED QUEEN STUDIO  
1/4" = 1'-0"



| REVISIONS |          |               |
|-----------|----------|---------------|
| No.       | Date     | Description   |
| 4         | 07/16/19 | Code Response |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |
|           |          |               |

Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated. 2011 MISHRA ARCHITECTURE PLLC



KEY PLAN

Pramukh Vicksburg.  
LLC

HOME2suites  
Vicksburg


Berryman Road  
Vicksburg, MS 39180

Drawing Title  
ELECTRICAL TYPICAL  
ROOM ENLARGED


Phase  
Construction Documents

|             |          |           |      |
|-------------|----------|-----------|------|
| Project No. | 19005    | Sheet No. | E302 |
| Prepared by | PTH      |           |      |
| Checked by  | RJH      |           |      |
| Date        | 04/02/19 |           |      |


Released for



1 KING STUDIO CONNECTING  
1/4" = 1'-0"




2 QUEEN STUDIO CONNECTOR  
1/4" = 1'-0"



3 FITNESS CENTER & GUEST LAUNDRY  
1/4" = 1'-0"



Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated.<sup>o</sup>  
2011 MISHRA ARCHITECTURE PLLC



## KEY PLAN

Pramukh Vicksburg.  
LLC

HOME2suits  
Vicksburg

Berryman Road  
Vicksburg, MS 39180

Drawing Title

ELECTRICAL ENLARGED  
FIRST FLOOR COMMON  
AREA

Phase  
Construction Documents


Project No. 19005

|             |     |
|-------------|-----|
| Prepared by | BTH |
|-------------|-----|

|            |      |
|------------|------|
| Checked by | PIII |
|------------|------|

Date 04/02/19

Released for



1 FIRST FLOOR PUBLIC AREAS  
1/4" = 1'-0"



Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated.<sup>®</sup>  
2011 MISHRA ARCHITECTURE PLLC

Pramukh Vicksburg.  
LLC


Berryman Road  
Vicksburg, MS 39180

Phase  
Construction Documents

Sheet No.

E401

Released fo



1 RISER AND ONE - LINE DIAGRAMS  
N.T.S.











Branch Panel: 2D

Location: Electrical 224

Supply From: MDP

Mounting: Surface

Enclosure: Type 1

Volts: 120/208 Wye

Phases: 3

Wires: 4

A.I.C. Rating: 10K

Mains Type:

Mains Rating: 250 A

MCB Rating:

Notes:

| CKT         | Circuit Description | Trip | Poles | A        |         | B        |         | C        |         | Poles | Trip | Circuit Description | CKT   |
|-------------|---------------------|------|-------|----------|---------|----------|---------|----------|---------|-------|------|---------------------|-------|
| 2D-1        | PANEL "A"           | 20 A | 2     | 7605...  | 7605... |          |         |          |         | 2     | 20 A | PANEL "A"           | 2D-2  |
| 2D-3        |                     |      |       |          |         | 6875...  | 6875... |          |         |       |      |                     | 2D-4  |
| 2D-5        | PANEL "A"           | 20 A | 2     | 6875...  | 6875... |          |         | 7605...  | 7605... | 2     | 20 A | PANEL "A"           | 2D-6  |
| 2D-7        |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-8  |
| 2D-9        | PANEL "A"           | 20 A | 2     |          |         | 7605...  | 7605... |          |         | 2     | 20 A | PANEL "A"           | 2D-10 |
| 2D-11       |                     |      |       |          |         |          |         | 6875...  | 6875... |       |      |                     | 2D-12 |
| 2D-13       | PANEL "A"           | 20 A | 2     | 7605...  |         |          |         |          |         |       |      |                     | 2D-14 |
| 2D-15       |                     |      |       |          |         | 6875...  |         |          |         |       |      |                     | 2D-16 |
| 2D-17       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-18 |
| 2D-19       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-20 |
| 2D-21       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-22 |
| 2D-23       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-24 |
| 2D-25       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-26 |
| 2D-27       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-28 |
| 2D-29       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-30 |
| 2D-31       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-32 |
| 2D-33       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-34 |
| 2D-35       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-36 |
| 2D-37       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-38 |
| 2D-39       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-40 |
| 2D-41       |                     |      |       |          |         |          |         |          |         |       |      |                     | 2D-42 |
| Total Load: |                     |      |       | 36566 VA |         | 35836 VA |         | 28961 VA |         |       |      |                     |       |
| Total Amps: |                     |      |       | 314 A    |         | 307 A    |         | 241 A    |         |       |      |                     |       |

Legend:

| Load Classification | Connected Load | Demand Factor | Estimated Demand | Panel Totals       |           |
|---------------------|----------------|---------------|------------------|--------------------|-----------|
| HVAC                | 42000 VA       | 100.00%       | 42000 VA         |                    |           |
| Motor               | 847 VA         | 103.57%       | 877 VA           | Total Conn. Load:  | 101363 VA |
| Other               | 0 VA           | 0.00%         | 0 VA             | Total Est. Demand: | 85165 VA  |
| Receptacle          | 25620 VA       | 69.52%        | 17810 VA         | Total Conn.:       | 281 A     |
| Lighting            | 1328 VA        | 125.00%       | 1660 VA          | Total Est. Demand: | 236 A     |
| Refrigerator        | 4305 VA        | 75.00%        | 3229 VA          |                    |           |
| Dishwasher          | 10500 VA       | 75.00%        | 7875 VA          |                    |           |
| Microwave           | 8400 VA        | 75.00%        | 6300 VA          |                    |           |

Notes:

PER NEC 220.84, THE DEMAND FACTOR FOR 6-7 MULTIFAMILY DWELLING UNITS IS 44%. THE CONNECTED LOAD AT 44% IS WELL BELOW THE 225A PANEL RATING. PANEL SCHEDULE IS TYPICAL FOR 3D & 4D.

Branch Panel: PANEL "A"

Location: King Studio 146

Supply From: 1A

Mounting: Surface

Enclosure: NEMA 1

Volts: 120/240 Single

Phases: 1

Wires: 3

A.I.C. Rating: 10K

Mains Type: MCB

Mains Rating: 100 A

MCB Rating: 100 A

Notes:

| CKT         | Circuit Description | Trip | Poles | A       |         | B       |         | Poles | Trip | Circuit Description     | CKT  |  |  |  |
|-------------|---------------------|------|-------|---------|---------|---------|---------|-------|------|-------------------------|------|--|--|--|
| A-1         | Suite Lights        | 20 A | 1     | 211 VA  | 1500 VA |         |         | 1     | 20 A | Kitchenette Receptacles | A-2  |  |  |  |
| A-3         | Suite Receptacles   | 20 A | 1     |         |         | 995 VA  | 1500 VA | 1     | 20 A | Dishwasher              | A-4  |  |  |  |
| A-5         | Suite Receptacles   | 20 A | 1     | 1080 VA | 615 VA  |         |         | 1     | 20 A | Refrigerator            | A-6  |  |  |  |
| A-7         | Bathroom Receptacle | 20 A | 1     |         |         | 180 VA  | 1200 VA | 1     | 20 A | Microwave               | A-8  |  |  |  |
| A-9         | PTAC                | 2    |       | 3000 VA | 1200 VA |         |         | 1     | 20 A | Garbage Disposal        | A-10 |  |  |  |
| A-11        |                     |      |       |         |         | 3000 VA | 0 VA    | 1     | 20 A | Spare                   | A-12 |  |  |  |
| Total Load: |                     |      |       | 7605 VA |         | 6875 VA |         |       |      |                         |      |  |  |  |
| Total Amps: |                     |      |       | 63 A    |         | 57 A    |         |       |      |                         |      |  |  |  |

Legend:

| Load Classification | Connected Load | Demand Factor | Estimated Demand | Panel Totals                |
|---------------------|----------------|---------------|------------------|-----------------------------|
| HVAC                | 6000 VA        | 100.00%       | 6000 VA          |                             |
| Motor               | 121 VA         | 125.00%       | 151 VA           |                             |
| Other               | 0 VA           | 0.00%         | 0 VA             |                             |
| Receptacle          | 3660 VA        | 100.00%       | 3660 VA          | Total Conn. Load: 14480 VA  |
| Lighting            | 190 VA         | 125.00%       | 237 VA           | Total Est. Demand: 14557 VA |
| Refrigerator        | 615 VA         | 100.00%       | 615 VA           | Total Conn.: 60 A           |
| Dishwasher          | 1500 VA        | 100.00%       | 1500 VA          | Total Est. Demand: 61 A     |
| Microwave           | 1200 VA        | 100.00%       | 1200 VA          |                             |
|                     |                |               |                  |                             |

Notes:

Branch Panel: PANEL "B"

Location: King One Bedroom 147

Supply From: 1A

Mounting: Surface

Enclosure: NEMA 1

Volts: 120/240 Single

Phases: 1

Wires: 3

A.I.C. Rating: 10K

Mains Type: MCB

Mains Rating: 100 A

MCB Rating: 100 A

Notes:


| CKT  | Circuit Description     | Trip | Poles | A           |         | B        |         | Poles | Trip | Circuit Description | CKT  |
|------|-------------------------|------|-------|-------------|---------|----------|---------|-------|------|---------------------|------|
| B-1  | Suite Lighting          | 20 A | 1     | 120 VA      | 1200 VA |          |         | 1     | 20 A | Garbage Disposal    | B-2  |
| B-3  | Kitchenette Receptacles | 20 A | 1     |             |         | 1500 VA  | 615 VA  | 1     | 20 A | Refrigerator        | B-4  |
| B-5  | Bathroom Receptacle     | 20 A | 1     | 180 VA      | 1500 VA |          |         | 1     | 20 A | Dishwasher          | B-6  |
| B-7  | Suite Receptacles       | 20 A | 1     |             |         | 1535 VA  | 816 VA  | 1     | 20 A | Bedroom Receptacles | B-8  |
| B-9  | Suite PTAC              | 20 A | 2     | 3000 VA     | 1200 VA |          |         | 1     | 20 A | Microwave           | B-10 |
| B-11 |                         |      |       |             |         | 3000 VA  | 3000 VA |       |      |                     |      |
| B-13 | Spare                   | 20 A | 1     | 0 VA        | 3000 VA |          |         | 2     | 20 A | Bedroom PTAC        | B-12 |
| B-15 | Spare                   | 20 A | 1     |             |         | 0 VA     | 0 VA    | 1     | 20 A | Spare               | B-14 |
| B-17 | Space                   | --   | --    | 0 VA        | 0 VA    |          |         | --    | --   | Space               | B-16 |
|      |                         |      |       | Total Load: |         | 10199 VA |         |       |      | 10465 VA            |      |
|      |                         |      |       | Total Amps: |         | 85 A     |         |       |      | 87 A                |      |

Legend:

| Load Classification | Connected Load | Demand Factor | Estimated Demand | Panel Totals            |          |
|---------------------|----------------|---------------|------------------|-------------------------|----------|
| HVAC                | 12000 VA       | 100.00%       | 12000 VA         |                         |          |
| Motor               | 50 VA          | 125.00%       | 63 VA            |                         |          |
| Other               | 0 VA           | 0.00%         | 0 VA             |                         |          |
| Receptacle          | 3840 VA        | 100.00%       | 3840 VA          | Total Conn. Load:       | 20664 VA |
| Lighting            | 270 VA         | 125.00%       | 337 VA           | Total Est. Demand:      | 20741 VA |
| Refrigerator        | 615 VA         | 100.00%       | 615 VA           | Total Conn.: 86 A       |          |
| Dishwasher          | 1500 VA        | 100.00%       | 1500 VA          | Total Est. Demand: 86 A |          |
| Microwave           | 1200 VA        | 100.00%       | 1200 VA          |                         |          |
|                     |                |               |                  |                         |          |
|                     |                |               |                  |                         |          |
|                     |                |               |                  |                         |          |
|                     |                |               |                  |                         |          |
|                     |                |               |                  |                         |          |
|                     |                |               |                  |                         |          |
|                     |                |               |                  |                         |          |
|                     |                |               |                  |                         |          |
|                     |                |               |                  |                         |          |

Notes:





6800 S Creek Rd, Charlotte, NC 28277  
Ph:(704) 625-6554 Fax:(704) 919-5822  
EMAIL:ashish@mishraarch.com  
WEB: www.mishraarch.com

**CIVIL:**  
Benchmark Engineering and Surveying  
101 Highpointe Court, Suite B  
Brandon, MS 39042  
Phone: (601) 591-1077  
Fax: (601) 591-0177  
Email:mikebes@bellsouth.net

**STRUCTURAL:**  
Whisonant Engineering Services, LLC  
122 Nut Tree Court  
Lexington, SC 29074  
Phone: (803) 957-4008  
Email: bill@weslex.com

**MEP:**  
Innovative Engineering Services, LLC  
2787 Stage Center DR., Suite 101  
Bartlett, TN 38134  
Phone: (901) 379-0500  
Email: [rherter@innovativees-llc.com](mailto:rherter@innovativees-llc.com)

Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated.  
2011 MISHRA ARCHITECTURE PLLC



Pramukh Vicksburg.  
LLC

HOME2suites  
Vicksburg

Berryman Road  
Vicksburg, MS 39180

Drawing Title

## ELECTRICAL - LEGEND, NOTES, & SPECS

Phase  
Construction Documents

|             |          |                       |
|-------------|----------|-----------------------|
| Project No. | 19005    | Sheet No.<br><br>E406 |
| Prepared by | PTH      |                       |
| Checked by  | RJH      |                       |
| Date        | 04/02/19 |                       |

Released for

## ELECTRICAL LEGEND

**FIRE ALARM**

**F**  FIRE ALARM SPEAKER & ADA SIGNAL LIGHT (80" MH)

**F**  FIRE ALARM HORN & ADA SIGNAL LIGHT (80" MH)

**F**  FIRE ALARM CHIME & ADA SIGNAL LIGHT (80" MH)

**L** FIRE ALARM ADA VISUAL SIGNAL LIGHT (80" MH)

 CEILING MOUNTED FIRE ALARM SPEAKER & SIGNAL LIGHT

 CEILING MOUNTED FIRE ALARM HORN & SIGNAL LIGHT

 CEILING MOUNTED FIRE ALARM SPEAKER

 CEILING MOUNTED FIRE ALARM ADA VISUAL SIGNALING LIGHT

**F** FIRE ALARM SIGNAL PULL STATION (46" MH)

**S** CEILING MOUNTED SMOKE DETECTOR

**H** WALL MOUNTED HORN/STROBE

**S** DUCT MOUNTED SMOKE DETECTOR

**SR** DUCT MOUNTED DETECTOR REMOTE TEST STATION AND ALARM INDICATOR LIGHT, WALL MOUNTED AT 80" MH, UNLESS NOTED OTHERWISE.

**D** ELECTROMAGNETIC DOOR HOLDER (WALL MOUNTED)

**R** FIRE ALARM CONTROLLED PROGRAMMABLE RELAY

**V** VALVE TAMPER SWITCH

**SD** SMOKE DAMPER

**FS** FIRE SHUTTER

**ANNP** ANNUNCIATOR PANEL

## COMMUNICATIONS

|                                                                                     |                                                                                                  |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|    | DATA OUTLET WITH 3/4" CONDUIT TO NEAREST ACCESSIBLE CEILING SPACE                                |
|    | TELEPHONE OUTLET WITH 3/4" CONDUIT TO NEAREST ACCESSIBLE CEILING SPACE                           |
|    | COMBINATION TELEPHONE/DATA OUTLET IN FLOOR WITH 3/4" CONDUIT TO NEAREST ACCESSIBLE CEILING SPACE |
|    | MICROPHONE OUTLET IN WALL                                                                        |
|    | MICROPHONE OUTLET IN FLOOR                                                                       |
|    | CEILING MOUNTED SPEAKER                                                                          |
|  | DOORBELL      |

## ELECTRICAL ABBREVIATIONS

| SYMBOL | DESCRIPTION                  |
|--------|------------------------------|
| A      | AMPERE                       |
| AF     | ABOVE FINISHED FLOOR         |
| AFG    | ABOVE FINISHED GRADE         |
| AI     | AMPERE INTERRUPTING CURRENT  |
| ANN    | ANNUNCIATOR                  |
| AUX    | AUXILIARY                    |
| AWG    | AMERICAN WIRE GAUGE          |
| C      | CONDUIT                      |
| CB     | CIRCUIT BREAKER              |
| CKT    | CIRCUIT                      |
| CLP    | CURRENT LIMITING PANEL       |
| CT     | CURRENT TRANSFORMER          |
| CU     | COPPER                       |
| DISC   | DISCONNECT                   |
| EDF    | ELECTRIC DRINKING FOUNTAIN   |
| FAAP   | FIRE ALARM ANNUNCIATOR PANEL |
| FACP   | FIRE ALARM CONTROL PANEL     |
| FL     | FULL LOAD AMPS               |
| G      | GROUND                       |
| GFI    | GROUND FAULT CURRENT         |
| HZ     | HERTZ                        |
| HP     | HORSEPOWER                   |
| KCMIL  | KILOVOLT-AMPERE              |
| KVA    | THOUSAND CIRCULAR MILS       |
| KV     | KILOVOLT-AMPERE              |
| LED    | KILOWATT                     |
| MCC    | LIGHT EMITTING DIODE         |
| N      | MAIN CONTROL CENTER          |
| NL     | MAIN LUGS ONLY               |
| NEC    | NEUTRAL                      |
| PF     | NATIONAL ELECTRIC CODE       |
| SOBW   | POWER FACTOR                 |
| VGW    | SPACE ONLY WITH BUS          |
| V      | UNDERGROUND ELECTRICAL       |
| VA     | VOLT                         |
| VPD    | VOLT-AMPERE                  |
| WFD    | VARIABLE FREQUENCY DRIVE     |
| WFMFR  | WEATHER PROOF                |
| 3P     | TRANSFORMER                  |
| 3PH    | THREE POLE                   |
| 3P3    | THREE PHASE                  |
| 4W     | FOUR WIRE                    |
| 30/40  | 30 AMPERE 40 AMP             |

**GENERAL PROJECT NOTES:**

1. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH DIVISION 26 SPECIFICATIONS, NATIONAL ELECTRICAL CODE, AND ALL OTHER APPLICABLE STANDARDS AND REGULATIONS ENFORCED BY THE AUTHORITY HAVING JURISDICTION.
2. ALL ABOVE GROUND EXTERIOR CONDUIT SHALL BE GALVANIZED RIGID STEEL CONDUIT WITH CORROSION RESISTANT FITTINGS, CLAMPS AND SUPPORT. INTERIOR EXPOSED CONDUIT ABOVE GROUND SHALL BE EMT.
3. IN THE EVENT OF CONFLICTS BETWEEN THE DRAWINGS, SPECIFICATIONS, CODES AND REGULATIONS, NOTIFY THE ARCHITECT IN WRITING FOR ENGINEER OF RECORD'S OPINION PRIOR TO INSTALLATION.
4. SHOP DRAWINGS SHALL BE SUBMITTED TO THE ARCHITECT FOR APPROVAL AND TO THE ENGINEER FOR REVIEW.
5. SMACNA SEISMIC RESTRAINT MANUAL, THIRD EDITION 2008, OR LATEST REVISION MAY BE USED AS A GUIDE FOR GENERAL SEISMIC SUPPORT DETAIL AND SUPPORT SPACING RECOMMENDATIONS.
6. COORDINATE LOCATION OF ALL LIGHTING FIXTURES, MECHANICAL EQUIPMENT AND ACCESS PANELS WITH OTHER DISCIPLINES PRIOR TO ROUGH-IN.
7. WHILE GREAT EFFORT HAS BEEN MADE TO IDENTIFY EXISTING CIRCUITS THAT ARE TO BE REMOVED OR REPLACED, THE INFORMATION MAY NOT BE ACCURATE.
8. ELECTRICAL CONTRACTOR SHALL VERIFY VOLTAGE AND AMP DRAW FOR ALL NEW EQUIPMENT.

| LIGHTING FIXTURE SCHEDULE |                                  |                                                      |                    |                    |       |                       | INNOVATIVE • ENGINEER SERVICES, L L C                                                                                                                                              |
|---------------------------|----------------------------------|------------------------------------------------------|--------------------|--------------------|-------|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MARK                      | MFG'R                            | CATALOG NUMBER                                       | LAMPS              |                    | VOLTS | MOUNTING              | REMARKS                                                                                                                                                                            |
|                           |                                  |                                                      | QTY.               | W. & TYPE          |       |                       |                                                                                                                                                                                    |
| A                         | OWNER FURN. CONTRACTOR INSTALLED | OWNER FURN. CONTRACTOR INSTALLED                     | TO BE DETER-MIN ED | 100W. MAX          | 120V. | WALL MTD.             | FLOUORESCENT WALL BRACKET IN GUEST ROOM CORRIDORS -- VERIFY MOUNTING HEIGHT WITH ARCHITECT.                                                                                        |
| B                         | LITHONIA LIGHTING                | LDN6 35/15 L06AR 120                                 |                    | LED                | 120V. | RECESS                | LED DOWNLIGHT WITH UL WET LABEL - PROVIDE EMERGENCY BATTERY BACK-UP WHERE SHADED.                                                                                                  |
| C                         | LITHONIA LIGHTING                | LDN6 35/15 L06AR 120                                 |                    | LED                | 120V. | RECESS                | LED DOWNLIGHT IN GUESTROOM ENTRY                                                                                                                                                   |
| D                         | OWNER FURN. CONTRACTOR INSTALLED | OWNER FURN. CONTRACTOR INSTALLED                     | 2                  | 32W T8             | 120V. | WALL MTD ABOVE MIRROR | 48" WALL MOUNTED FLOUORESCENT FIXTURE -- MTD ON WALL ABOVE GUEST BATHROOM MIRROR                                                                                                   |
| D1                        | OWNER FURN. CONTRACTOR INSTALLED | OWNER FURN. CONTRACTOR INSTALLED                     | TO BE DETERMIN ED  | 100W. MAX.         | 120V. | PENDANT               | DECORATIVE PENDANT FIXTURE IN RESTROOMS                                                                                                                                            |
| D2                        | OWNER FURN. CONTRACTOR INSTALLED | OWNER FURN. CONTRACTOR INSTALLED                     | TO BE DETERMIN ED  | 500W. MAX          | 120V. | PENDANT               | DECORATIVE PENDANT IN LOBBY OASIS                                                                                                                                                  |
| D3                        | OWNER FURN. CONTRACTOR INSTALLED | OWNER FURN. CONTRACTOR INSTALLED                     | TO BE DETERMIN ED  | 100W MAX.          | 120V. | PENDANT               | DECORATIVE PENDANT IN BUSINESS CENTER                                                                                                                                              |
| D4                        | OWNER FURN. CONTRACTOR INSTALLED | OWNER FURN. CONTRACTOR INSTALLED                     | 2                  | 17W T8             | 120V. | WALL MTD ABOVE MIRROR | 24" WALL MOUNTED. FLOUORESCENT FIXTURE -- MOUNT ON WALL ABOVE MIRROR IN PUBLIC RESTROOMS                                                                                           |
| EH                        | COOPER SURE-LITES                | APLC7R6                                              | N/A                | LED                | 120V. | WALL MTD.             | COMBINATION EXIT SIGN AND TWIN HEAD EMERGENCY LIGHT                                                                                                                                |
| EM                        | LITHONIA                         | EU2L-M12                                             | N/A                | LED                | 120V. | WALL MTD.             | TWIN HEAD EMERGENCY LIGHT                                                                                                                                                          |
| ER                        | LITHONIA                         | ECC-R-REM-M6                                         | N/A                | LED                | 120V. | WALL MTD.             | WEATHERPROOF REMOTE-MOUNT EMERGENCY LIGHT                                                                                                                                          |
| EX                        | LITHONIA                         | ERE-GY-SGL-WP                                        | N/A                | LED                | 120V. | WALL MTD.             | EXIT SIGN, SINGLE OR DOUBLE FACE, ARROWS AS REQUIRED                                                                                                                               |
| G                         | MARK LIGHTING                    | SPRL 4 G9 N35AS FA NX 120                            |                    | LED                | 120V. | COVE                  | RECESSED LED COVE LIGHT                                                                                                                                                            |
| H                         | LITHONIA LIGHTING                | 2GTL4 LP835                                          |                    | LED                | 120V. | RECESS                | 2 X 2 LAY-IN FLOUORESCENT PARABOLIC TROFFER -- FURNISH WITH FLANGE KIT WHERE NECESSARY                                                                                             |
| K                         | LITHONIA LIGHTING                | WL4 41L D43 LP835 N80 NSPDT7 DIM50                   |                    | LED                | 120V. | WALL MTD.             | WALL MOUNTED FLOUORESCENT FIXTURE IN STAIRWELL                                                                                                                                     |
| L                         | LITHONIA LIGHTING                | LBL4 LP835                                           |                    | LED                | 120V. | SURFACE               | WRAP AROUND SURFACE MOUNTED FLOUORESCENT                                                                                                                                           |
| M                         | LITHONIA LIGHTING                | 2MPL3N G A 3 32 18LD MVL0T 1/3 GEB10PS PWS1836 LP835 |                    | LED                | 120V. | RECESS                | 2 X 4 LAY-IN FLOUORESCENT TROFFER -- FURNISH WITH FLANGE KIT WHERE NECESSARY                                                                                                       |
| N                         | LITHONIA LIGHTING                | LDN6 35/15 L06AR 120                                 |                    | LED                | 120V. | RECESS                | LED DIRECTIONAL EYEBALL                                                                                                                                                            |
| P                         | HALO (COOPER)                    | CLHET2010400 LV-1419SN                               | 1                  | MR16               | 120V. | RECESS                | LOW VOLTAGE PINHOLE DOWNLIGHT -- OVER REGISTRATION DESK                                                                                                                            |
| Q                         | DESIGN PLAN                      | LD6-L 4SS1G                                          | 1                  | LED 1F-1WX6        | 120V. | RECESS                | RECESS DOWNLIGHT IN SOFFIT -- UL WET LABEL                                                                                                                                         |
| R                         | LITHONIA LIGHTING                | LDN6 35/15 L06AR 120                                 |                    | LED                | 120V. | RECESS                | RECESSED LOW CLEARANCE CANN -- SUBSTITUTE FOR "C" ON UPPER FLOOR ELEVATOR LOBBY WITH LOW CLEARANCE                                                                                 |
| S                         | LITHONIA LIGHTING                | OLVTWM                                               |                    | LED                | 120V. | WALL MTD.             | LED VAPORTITE IN ELEVATOR PIT                                                                                                                                                      |
| T                         | HADCO                            | WAB2 B CF226E                                        | 2                  | 25W CFL            | 120V. | WALL MTD.             | EXTERIOR BEACON UPLIGHTS -- MTD. ON BEACON STEEL BRACKETS -- VERIFY MTG HEIGHT WITH ARCHITECT                                                                                      |
| W                         | LITHONIA                         | FM4711 GL 10 WH                                      | 2                  | 13W, DTT           | 120V. | WALL MTD.             | WALL MOUNTED FLOUORESCENT FIXTURE -- MOUNT ABOVE DOOR ON HEADER IN EQUIPMENT AND STORE ROOMS                                                                                       |
| X                         | SEE SYMBOLS LEGEND               | SEE SYMBOLS LEGEND                                   | N/A                | SEE SYMBOLS LEGEND | 120V. | SEE SYMBOLS LEGEND    | SEE SYMBOLS LEGEND                                                                                                                                                                 |
| OA                        | HYDREL                           | TPS1 18LED WHT41K MFL YMBL MVOLT WMTL LP             |                    | LED                | 120V. | WALL MTD.             | LED EXTERIOR WALL SCONCE WITH WET UL LABEL -- VERIFY MOUNTING HEIGHT WITH ARCHITECT.                                                                                               |
| OB                        | BEGA                             | 3308LED                                              |                    | LED                | 120V. | WALL MTD.             | LED EXTERIOR WALL PACK WITH WET UL LABEL -- VERIFY MOUNTING HEIGHT WITH ARCHITECT.                                                                                                 |
| OC                        | LITHONIA LIGHTING                | WST LED 1 10A700/40K SR4 MVOLT DDBXD                 |                    | LED                | 120V. | WALL MTD.             | LED EXTERIOR WALL SCONCE WITH WET UL LABEL -- VERIFY MOUNTING HEIGHT WITH ARCHITECT.                                                                                               |
| OD                        | HYDREL                           | M9710 A 18LED WKT41K MVOLT MFL FLC20 34B             |                    | LED                | 120V. | IN GROUND FLOOD       | MTD. IN-GROUND FIXT. 2'-0" FROM FLAGPOLE OR WALL IN CONCRETE IN STRICT ACCORDANCE WITH MFG'RS WRITTEN RECOMMENDATIONS.                                                             |
| OE                        | HYDREL                           | M9710 A 18LED WKT41K MVOLT MFL FLC20 34B             |                    | LED                | 120V. | IN GROUND FLOOD       | MTD. IN-GROUND FIXT. 2'-0" FROM FLAGPOLE OR WALL IN CONCRETE IN STRICT ACCORDANCE WITH MFG'RS WRITTEN RECOMMENDATIONS.                                                             |
| OF                        | AMERICAN LIGHTING                | LS-MS-24-100BK                                       | 1 LOT              | LEDBS14-8WW        | 120V. | SURFACE STRING        | STRING LIGHTS                                                                                                                                                                      |
| OG                        | LITHONIA LIGHTING                | DSX0 LED 40C 1000 40K T4M MVOLT SPA DDBXD            |                    | LED                | 208V. | POLE                  | 1-LED ARCHITECTURAL ARM MTD. CUTOFF LUMINAIRE -- PROVIDE 20 FT. POLE -- POLE FINISH TO MATCH FIXTURE -- POLE SHALL MEET 120 MPH WIND REQUIREMENTS -- MT. ON CONCRETE BASE 3FT THAT |
| OH                        | LITHONIA LIGHTING                | DSX0 LED 40C 1000 40K T4M MVOLT SPA DDBXD            |                    | LED                | 208V. | POLE                  | 3-LED ARCHITECTURAL ARM MTD. CUTOFF LUMINAIRE -- PROVIDE 20 FT. POLE -- POLE FINISH TO MATCH FIXTURE -- POLE SHALL MEET 120 MPH WIND REQUIREMENTS -- MT. ON CONCRETE BASE 3FT THAT |
| OK                        | LITHONIA LIGHTING                | DSXW1LED 20C 700 40K T4M MVOLT DDBXD                 |                    | LED                | 120V. | WALL MTD.             | LED EXTERIOR WALL SCONCE WITH WET UL LABEL -- VERIFY MOUNTING HEIGHT WITH ARCHITECT.                                                                                               |
| FFE1                      | WALL SCONCE                      | WALL SCONCE                                          | 1                  | 100W MAX.          | 120V. | WALL                  | FURNISHED BY F.F.E. SUPPLIER - INSTALLED BY ELECTRICAL CONTRACTOR                                                                                                                  |

NOTES:

- 1.) INTERIOR COLOR TEMPERATURE SHALL BE WARM WHITE.
- 2.) ALLEXTERIOR FIXTURES SHALL BE LABELED "WET" OR "DAMP" LOCATIONS AS DETERMINED BY THEIR LOCATIONS
- 3.) ALLPOOL AREA CIRCUITS SHALL BE EQUIPPED WITH GFC PROTECTION.
- 4.) VERIFY ALL MOUNTING HEIGHTS WITH ARCHITECT PRIOR TO ROUGH-IN.

7/17/2019 8:07:35 PM

HOME2suites Vicksburg





SPECIFICATIONS & NOTES

- GENERAL:** FURNISH ALL LABOR, EQUIPMENT, AND MATERIALS NECESSARY FOR A COMPLETE INSTALLATION OF ELECTRICAL WIRING. THE DRAWINGS INDICATE DIAGRAMMATICALLY THE EXTENT, GENERAL CHARACTER, AND THE APPROXIMATE LOCATION OF THE WORK TO PERFORMED. OMISSIONS OF THE DETAILS OF WORK, MOUNTING HARDWARE, FITTING, J-BOXES, OUTLET BOXES, PULL BOXES, SUPPORTS, CONNECTORS, ACCESSORIES, AND/OR ADAPTORS WHICH ARE EVIDENTLY NECESSARY TO CARRY OUT THE INTENT OF THE DRAWINGS AND SPECIFICATIONS, SHALL BE PROVIDED. CONNECT ALL ELECTRICAL EQUIPMENT WHETHER FURNISHED BY ELECTRICAL CONTRACTOR OR BY OTHERS AND WHETHER SHOWN ON PLANS OR NOT. INSTALL AND CONNECT ALL STARTERS FURNISHED BY THIS CONTRACTOR OR OTHERS. FURNISH, INSTALL, AND CONNECT DISCONNECTS AND SAFETY SWITCHES FOR ALL ELECTRICAL EQUIPMENT WHETHER FURNISHED BY THIS CONTRACTOR OR OTHERS AND WHERE REQUIRED BY NEC. BEFORE INSTALLING RACEWAYS FOR MOTORS, APPLIANCES, HVAC AND/OR OTHER EQUIPMENT PROVIDED BY OTHERS VERIFY LOCATIONS AND ARRANGE RACEWAYS ACCORDINGLY. VERIFY ALL DOOR SWINGS WITH ARCHITECTURAL PLANS BEFORE ROUGHING IN LIGHT SWITCHES. WHERE NO RACEWAY SIZES OR WIRE SIZES ARE SHOWN INSTALL AS REQUIRED BY NEC. VERIFY POWER AND CONNECTION REQUIREMENTS FOR ALL EQUIPMENT BEFORE INSTALLATION. WIRE AS REQUIRED BY EQUIPMENT MANUFACTURER AND IN COMPLIANCE WITH NEC. OBTAIN MOCP AND MCA INFORMATION FROM ACTUAL EQUIPMENT BEING INSTALLED AND CIRCUIT ACCORDINGLY. ALL CIRCUIT BREAKERS SUPPLYING HVAC EQUIPMENT SHALL BE HACR TYPE. ALL WORK SHALL COMPLY WITH APPLICABLE LAWS OF THE COMMUNITY AND WITH THE NEC. OBTAIN AND PAY FOR ALL PERMITS REQUIRED. OBTAIN APPROVAL FOR ALL WORK INDICATED ON PLANS AND IN SPECIFICATIONS FROM ALL AGENCIES AND AUTHORITIES HAVING JURISDICTION. AFTER COMPLETION OF THE WORK, SUBMIT CERTIFICATE OF FINAL INSPECTION AND APPROVAL FROM THE LOCAL ELECTRICAL INSPECTOR AND LOCAL FIRE DEPARTMENT AUTHORITIES CERTIFYING THAT THE INSTALLATION COMPLIES WITH ALL REGULATIONS GOVERNING THE SAME. ALL MATERIALS SHALL BE NEW AND UL LISTED. EXECUTE ALL WORK IN A WORKMANLIKE MANNER SO AS TO PRESENT A NEAT AND MECHANICAL APPEARANCE WHEN COMPLETED.
- COORDINATION:** COORDINATE WORK SO AS TO CONFORM TO THE PROGRESS OF THE WORK OF THE OTHER TRADES, AND COMPLETE THE ENTIRE INSTALLATION AS SOON AS THE CONDITION OF THE BUILDING PERMITS. SOME SAFETY DISCONNECT SWITCHES MAY BE PROVIDED BY THE MECHANICAL CONTRACTOR BUT INSTALLED AND CONNECTED BY THE ELECTRICAL CONTRACTOR. THE WORK SHALL BE COORDINATED BY THE ELECTRICAL CONTRACTOR.
- INTERFERENCE:** IN THE EVENT THAT INTERFERENCES OR CONFLICTS DEVELOP, THE ARCHITECT SHALL DECIDE WHICH EQUIPMENT SHALL BE RELOCATED AT NO COST TO OWNER REGARDLESS OF WHICH WAS FIRST INSTALLED.
- CUTTING AND PATCHING:** PROVIDE CUTTING AND PATCHING, UNDER THE SUPERVISION OF THE GENERAL CONTRACTOR, AS REQUIRED FOR ELECTRICAL WORK. COORDINATE WITH OTHER TRADES AS WORK PROGRESSES SO CUTTING AND PATCHING WILL NOT BE REQUIRED OR BE MINIMAL.
- SUBMITTALS:** WITHIN TWENTY (20) DAYS AFTER AWARD OF CONTRACT, SUBMIT SIX (6) COPIES OF MANUFACTURER'S DRAWINGS TO THE ARCHITECT FOR REVIEW OF THE FOLLOWING ITEMS: PANELBOARDS, LIGHT FIXTURES, DISCONNECT SWITCHES, FIRE ALARM SYSTEM (COMPLETE WITH PLAN SHOWING WIRING/ CONDUIT).
- TESTING:** UPON COMPLETION OF THE WORK, CONDUCT A THOROUGH TEST IN THE ARCHITECT'S PRESENCE, AND SHOW THE ENTIRE SYSTEM TO BE IN PERFECT WORKING CONDITION.
- GUARANTEE:** GUARANTEE THAT ALL WORK EXECUTED UNDER THESE SPECIFICATIONS AND PLANS WILL BE FREE FROM DEFECTS OF WORKMANSHIP AND MATERIALS FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF FINAL ACCEPTANCE OF THIS WORK. PROMPTLY REPAIR, REPLACE, OR OTHERWISE MAKE GOOD, UPON NOTIFICATION, ANY DEFECT BECOMING APPARENT DURING THIS PERIOD, AT NO COST TO THE OWNER.
- TEMPORARY SYSTEMS:** THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR FURNISHING AND INSTALLING EQUIPMENT AND MATERIALS NECESSARY FOR PROVIDING ELECTRICAL POWER WHERE NEEDED FOR THE CONSTRUCTION OF THE PROJECT IN ACCORDANCE WITH ALL OSHA REGULATIONS.
- SITE VISIT:** BEFORE SUBMITTING A BID, VISIT THE SITE AND VERIFY ALL EXISTING CONDITIONS. MAKE SUCH ADJUSTMENTS TO WORK AS REQUIRED BY THE ACTUAL CONDITIONS ENCOUNTERED.
- SERVICE ENTRANCE:** IT SHALL BE THE RESPONSIBILITY OF THIS CONTRACTOR TO VERIFY THAT THE LOCATION, ARRANGEMENT, VOLTAGE, PHASE AND CONNECTIONS TO UTILITY SERVICE, AS WELL AS THE REQUIRED METERING EQUIPMENT, ARE COORDINATED WITH AND IN ACCORDANCE WITH REQUIREMENTS OF THE LOCAL POWER COMPANY. IF THE REQUIREMENTS ARE AT VARIANCE WITH THESE DRAWINGS OR SPECIFICATIONS, THE CONTRACT PRICE SHALL INCLUDE ANY ADDITIONAL COST NECESSARY TO MEET THOSE REQUIREMENTS WITHOUT EXTRA COST TO THE OWNER AFTER THE CONTRACT IS ENTERED INTO. NOTIFY ARCHITECT OF ANY CHANGES REQUIRED BEFORE PROCEEDING WITH WORK. ANY CHARGES BY THE UTILITY COMPANY FOR THE ELECTRICAL SERVICE TO THE FACILITY SHALL BE INCLUDED IN THE BID PRICE.
- CONDUIT PENETRATIONS:** WHERE CONDUITS AND OTHER ELECTRICAL EQUIPMENT RACEWAYS PASS THROUGH FIRE PARTITIONS, FIRE WALLS, OR FLOORS, INSTALL A FIRE STOP THE PROVIDES AN EFFECTIVE BARRIER AGAINST THE SPREAD OF FIRE, SMOKE, AND GASES AND WHICH MAINTAINS THE FIRE RATING OF THE WALL WHICH HAS BEEN PENETRATED. WHERE EXTERIOR WALLS OR FLOORS ARE PENETRATED PROVIDE COMPLETELY WEATHERPROOFING OF PENETRATION. FURNISH ROOF FLASHING FOR ALL CONDUIT OR EQUIPMENT WHICH PENETRATES ROOF.
- LIGHT FIXTURES:** IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY THE EXACT TYPE CEILING, TYPE FIXTURE MOUNTING AND TRIM, AND RECESSING DEPTH OF ALL RECESSED FIXTURES PRIOR TO PURCHASING ANY FIXTURES. REGARDLESS OF PART NUMBERS IDENTIFIED ON THE LIGHT FIXTURE SCHEDULE, IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY THE PROPER OPERATING VOLTAGE OF LIGHT FIXTURES ACCORDING TO THE PLANS PRIOR TO PURCHASING ANY FIXTURES. EQUIVALENT FIXTURES SUBSTITUTES BY LITHONIA, COOPER LIGHTING, AND HUBBELL WILL BE ACCEPTED. PROVIDE LAMPS FOR ALL FIXTURES. LAMPS SHALL BE MANUFACTURED BY GE, OSRAM- SYLVANIA, OR PHILIPS. FLUORESCENT BALLASTS SHALL BE HIGH FREQUENCY ELECTRONIC TYPE BY MAGNETIC TRIAD, LUTRON, OSRAM- SYLVANIA OR MOTOROLA AND SHALL HAVE A 5 YEAR WARRANTY. BF SHALL BE GREATER THAN .9, THD SHALL BE LESS THAN 20%, CF GREATER THAN 1.7 AND PF GREATER THAN .93. HID LAMPS BALLASTS SHALL BE HIGH POWER FACTOR (.90 OR GREATER) TYPE. HID LAMPS SHALL BE CERAMIC TYPE. PROVIDE ALL MOUNTING HARDWARE, ADAPTORS, AND ACCESSORIES AS REQUIRED. UOM, CENTER ALL DOWNLIGHTS AND WALLWASHERS ON CEILING TILE.
- BUILDING WIRES & CABLE:** INTERIOR WIRE SHALL BE COPPER THHN, #12 AWG MINIMUM TYPE "XHHW" COPPER SHALL BE USED EXTERIOR OR UNDERGROUND. CONDUCTORS #10 AND #12 SHALL BE SOLID. LARGER SIZES SHALL BE STRANDED. CONTROL AND SIGNAL WIRE SHALL BE TYPE "TFF" COPPER, MINIMUM SIZE #16. JOINTS AND SPLICES IN WIRE SHALL BE MADE WITH SOLDERLESS CONNECTORS, AND COVERED SO THAT INSULATION IS EQUAL TO CONDUCTOR INSULATION. WIRE NUTS SHALL NOT BE USED FOR CONDUCTOR #8 AND LARGER. NO SPLICES SHALL BE PULLED INTO CONDUIT. BOTH IN CONNECTORS AND CONDUITS SHALL BE CONTINUOUS FROM OUTLET TO OUTLET. ALL CONDUITS SHALL HAVE DUSHING WITH SMOOTH BEVELED THROATS INSTALLED AT BOTH ENDS PRIOR TO INSTALLING CONDUCTORS. CIRCUITS MAY BE COMBINED IF CONDUIT SIZES ARE ADJUSTED WHERE NECESSARY AND NEC DERATING FACTORS ARE OBSERVED. BRANCH CIRCUIT WIRE GAUGES SHALL BE INCREASED AS REQUIRED FOR A MAXIMUM OF 3% VOLTAGE DROP. TYPE MC CABLE MAY BE USED AS PERMITTED BY ARTICLE 330 OF NEC.
- CONDUIT:** ALL WIRING SHALL BE IN RACEWAYS, MINIMUM 1/2" DIAMETER. USE EMT FOR GENERAL INTERIOR WORK. RIGID GALVANIZED STEEL OR INTERMEDIATE METAL CONDUIT SHALL BE USED IN FLOOR SLABS, WHERE EMBEDDED IN CONCRETE, AREAS EXPOSED TO MOISTURE, AREAS IN DANGER OF MECHANICAL INJURY AND HAZARDOUS AREAS. PVC SCHEDULE 40 (3/4" MINIMUM DIAMETER) SHALL BE USED BELOW GRADE WITH STEEL TRANSITIONS THRU SLABS. USE FLEXIBLE METAL CONDUIT CONNECTIONS TO MOTORS, TRANSFORMERS AND OTHER VIBRATING EQUIPMENT. EXTERIOR FLEW SHALL BE LIQUIDTIGHT. EMT CONDUIT FITTINGS SHALL BE SET-SCREW TYPE. ALL EXPOSED CONDUIT SHALL BE PAINTED TO MATCH SURFACE UPON WHICH IT IS INSTALLED. INTERIOR WIRING AS SHOWN ON PLANS WILL, TYPICALLY BE CONCEALED IN CEILINGS WALLS OR FLOORS EXCEPT IN MECHANICAL/ ELECTRICAL ROOMS, JANITOR CLOSETS, UNFINISHED ROOMS AND OTHER SUCH ROOM WHERE CONDUITS ARE TYPICALLY EXPOSED. WHERE NO RACEWAY SIZES OR WIRE SIZES ARE SHOWN ON PLAN PROVIDE AND INSTALL AS REQUIRED BY NEC.
- DEVICE PLATES:** COVER PLATES SHALL BE SMOOTH NYLON W/ COLOR MATCHING DEVICES. VERIFY COLOR W/ FF&E FINISH SCHEDULE. FOR UNFINISHED AREAS EXPOSED CONDUIT, COVER PLATES SHALL BE GALVANIZED STEEL WITH BEVELED EDGES.

1 SPECIFICATIONS & NOTES  
1/8" = 1'-0"

SPECIFICATIONS & NOTES

- FUSES: CLASS RK-1 TIME DELAY FUSE FOR PROTECTING CIRCUIT BREAKERS. BUSSMAN LIMTRON OR EQUAL. CLASS RK-5 TIME DELAY FUSE FOR PROTECTION OF MOTORS AND TRANSFORMERS. BUSSMAN FUSETRON OR EQUAL. 200K AIC AT RATED VOLTAGE.
- OUTLET BOXES: EXCEPT AS NOTED, BOXES SHALL BE STANDARD GALVANIZED OR SHERADIZED AT LEAST 1 1/2 INCHES DEEP OR AS NOTED IN PLANS. OF METAL AT LEAST 1 1/16 INCH THICK, SIZED TO ACCOMMODATE DEVICES AND CONDUCTOR AS PER NEC ARTICLE 370. COORDINATE DEPTH WITH WALL CONSTRUCTION. BOXES USED WITH EXPOSED CONDUIT SHALL BE 4-INCH SQUARE UTILITY BOXES. EXTERIOR BOXES SHALL BE GALVANIZED CAST-IRON WITH GASKETS AND APPROPRIATE FITTINGS. BOXES SHALL BE PROVIDED WITH APPROVED 3/8" FIXTURE STUDS WHERE REQUIRED. EXCEPT WHERE LOCATED IN CONCRETE BLOCK, SWITCH AND RECEPTACLE BOXES SHALL BE 4" SQUARE FOR SINGLE GANG INSTALLATION. APPROPRIATE GANG BOXES SHALL BE USED FOR MOUNTING GANGED SWITCHES.
- WIRING DEVICES: SWITCHES SHALL BE A.C. TYPE AS MADE BY HUBBELL, P & S, G.E. OR LEVITON. RECEPTACLES SHALL BE HUBBELL, BRYANT, P & S, G.E. OR LEVITON. COLOR SHALL BE SELECTED BY FF&E FINISH SCHEDULE. PROVIDE MATCHING PLUGS FOR SPECIAL PURPOSE RECEPTACLES WHEN REQUIRED FOR CONNECTION EQUIPMENT. ALL RECEPTACLES IN TOILETS, WITHIN 6 FT. OR SINKS, IN COMMERCIAL KITCHENS AND IN EXTERIOR LOCATIONS SHALL BE GFI TYPE. EXTERIOR RECEPTACLES SHALL HAVE WEATHERPROOF AND GASKETED COVERS. ALL RECEPTACLES IN GUEST ROOMS SHALL BE TAMPERPROOF.
- PANELBOARDS: PANELBOARDS SHALL BE OF A DEAD-FRONT SAFETY TYPE EQUIPPED WITH THERMAL MAGNETIC CASE CIRCUIT BREAKERS WITH FRAME AND TRIP RATINGS AS SHOWN ON THE SCHEDULE. CIRCUIT BREAKER SHALL BE QUICK-BREAK, QUICK-BREAK THERMAL MAGNETIC TRIPS INDICATING AND SHALL HAVE COMMON TRIP ON ALL MULTIPOLAR BREAKERS. CONNECTION TO THE BUSS SHALL BE BOLT ON. TERMINALS FOR FEEDER CONDUCTORS TO THE PANELBOARD MAINS AND NEUTRAL SHALL BE UL LISTED AS SUITABLE FOR THE TYPE OF CONDUCTOR SPECIFIED. TERMINALS FOR BRANCH CIRCUIT WIRING, BOTH BREAKER AND NEUTRAL, SHALL BE UL LISTED AS SUITABLE FOR THE CONDUCTOR SPECIFIED. PANELBOARDS NOT SHOWN TO BE RATED FOR SERVICE ENTRANCE SHALL BE EQUIPPED WITH AN ISOLATED NEUTRAL AND A GROUNDING BUSS. THE PANELBOARD FRONT SHALL BE OF HINGED FRONT TYPE WITH DOORS EQUIPPED WITH FLUSH-BRUSHED STEEL, CYLINDER TUMBLER-TYPE LOCKS WITH CATCHES AND SPRING-LOADED DOOR PULLS. THE FLUSH LOCK SHALL NOT PROTRUDE BEYOND THE FRONT OF THE DOOR. ALL PANELBOARD LOCKS SHALL BE KEYPED ALIKE. A CIRCUIT DIRECTORY FRAME AND CARD WITH CLEAR PLASTIC COVERING SHALL BE PROVIDED ON THE INSIDE OF THE DOOR. PANELBOARDS SHALL BE RATED FOR USE AS SERVICE ENTRANCE EQUIPMENT WHERE REQUIRED BY NEC. FOR ALL FLUSH INSTALLED PANELBOARDS, LEAVE EMPTY 3/4" CONDUITS STUBBED TO THE ABOVE CEILING SPACE. PANELBOARDS SHALL BE BY GENERAL ELECTRIC, SQUARE "D", OR CUTLER-HAMMER. LOAD CENTERS SHALL NOT BE USED UNLESS INDICATED ON PLANS.
- SAFETY SWITCHES/DISCONNECTS: SAFETY SWITCHES AND DISCONNECT SWITCHES SHALL BE TYPE "D" OR GENERAL ELECTRIC. DISCONNECT SWITCHES SHALL BE TYPE "D" OR GENERAL ELECTRIC. DISCONNECTS ADJACENT TO EQUIPMENT ON SUITABLE STRUCTURE. A DISCONNECT SHALL NOT BE REQUIRED OTHER THAN THE CB WHICH PROVIDES POWER TO EQUIPMENT WHEN THE EQUIPMENT IS WITHIN SIGHT AND NOT GREATER THAN 50 FEET FROM CB. VERIFY DISCONNECT SIZE FROM EQUIPMENT NAMEPLATE DATA. MOUNT DISCONNECTS FOR OUTSIDE HVAC UNITS NO HIGHER THAN HEIGHT OF UNIT. PROVIDE CLEARANCES AS REQUIRED BY NEC 110.26.
- GROUNDING: ALL EQUIPMENT SHALL BE GROUNDED AND BONDED IN ACCORDANCE WITH LOCAL REGULATIONS AND NATIONAL ELECTRICAL CODE. INSTALL A GREEN EQUIPMENT GROUNDING CONDUCTOR IN ALL RACEWAYS.
- COLOR CODING OF CONDUCTORS: COLOR CODE CONDUCTORS IN ACCORDANCE WITH THE NEC AND WITH STANDARD AND ACCEPTED TRADE PRACTICES.
- OUTLET BOX MOUNTING HEIGHTS: UNLESS OTHERWISE NOTED, WALL SWITCHES (GENERAL): 48" AFF. RECEPTACLES: 18" AFF. TELEPHONE WALL OUTLETS: 48" AFF. THERMOSTATS: 48" AFF.
- OUTLETS AND CONDUIT FOR OTHER TRADES: PROVIDE CONCEALED 4" SQUARE (OR SMALLER WHEN REQUIRED) JET BOXES WITH EMPTY PLUMBING CONTRACTORS. COORDINATE REQUIREMENTS WITH EACH CONTRACTOR. WHETHER SHOWN ON PLANS OR NOT, PROVIDE A WP, GFI RECEPTACLE LOCATED WITHIN 25" OF ALL EXTERIOR HVAC EQUIPMENT.
- VERIFY: THE WORD "VERIFY" WHEN USED IN PLANS SHALL MEAN TO VERIFY LOCATION AND WIRING REQUIREMENTS BEFORE CIRCUITING AND CIRCUIT IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND IN COMPLIANCE WITH NEC.
- DATA, CABLE TV, TELEPHONE: FOR CABLE TV OUTLETS, DATA OUTLETS, AND TELEPHONE OUTLETS THE WIRING, JACKS, AND FACEPLATES WILL BE PROVIDED BY OTHERS UNLESS OTHERWISE NOTED. MOUNT INDIVIDUAL DATA OUTLETS, TELEPHONE OUTLETS AND CABLE TV OUTLETS AT EXACTLY THE SAME HEIGHT AS RECEPTACLES UNLESS NOTED OTHERWISE.
- NEC: "NEC" REFERS TO THE LATEST EDITION OF THE NATIONAL ELECTRICAL CODE WHICH HAS BEEN ADOPTED INTO LOCAL BUILDING CODE BY AGENCIES AND AUTHORIZES HAVING JURISDICTION.
- EXTERIOR ENCLOSURES: ALL EXTERIORS ENCLOSURES OR ENCLOSURES EXPOSED TO MOIST CONDITIONS SHALL BE RATED NEMA 3R OR RATED FOR USE IN DAMP OR WET CONDITIONS AS EACH CASE REQUIRES.
- UNDERGROUND INSTALLATIONS: WHERE CONDUIT IS INSTALLED BELOW GRADE, THE MINIMUM BURIAL DEPTH SHALL BE 24" UNLESS INSTALLED UNDER BUILDING SLAB (WHERE THERE IS NO MINIMUM BURIAL DEPTH). WHERE RIGID CONDUIT IS INSTALLED BELOW GRADE, COAT CONDUIT AND COUPLINGS WITH (2) COATS OF ASPHALTUM PAINT. UNDERGROUND PRIMARY CONDUIT INSTALLED IN COORDINATION WITH POWER COMPANY SHALL BE INSTALLED AT DEPTH AS DIRECTED BY POWER COMPANY. AVOID ALL EXISTING UTILITIES. ANY EXISTING UTILITIES DAMAGED SHALL BE REPAIRED AT CONTRACTORS EXPENSE AND AS DIRECTED BY ARCHITECT. RESTORE ANY DAMAGE PAVING TO MATCH EXISTING.
- IDENTIFICATION: PROVIDE 1" HIGH LAMINATE PHENOLIC NAMEPLATES PERMANENTLY INSTALLED (WITH 3/8" HIGH WHITE LETTERS ON BLACK) ON THE FRONT OF ALL DISCONNECT SWITCHES, CB ENCLOSURES, PANELBOARDS, CONTACTORS, TRANSFORMERS, TRANSIENT VOLTAGE SURGE SUPPRESSORS AND STARTERS.
- CLEANING UP: DURING THE PROGRESS OF WORK, KEEP THE OWNER'S PREMISE IN A NEAT AND ORDERLY CONDITION, FREE FROM ACCUMULATION OF DEBRIS RESULTING FROM THIS WORK. AT THE COMPLETION OF THE WORK, REMOVE ALL MATERIAL, SCRAP, ETC. NOT A PART OF THIS CONTRACT.
- OPERATING & MAINTENANCE INSTRUCTIONS: TURN OVER TO THE ARCHITECT ONE SET OF ALL EQUIPMENT CATALOGS AND MAINTENANCE DATA. EXPLAIN AND DEMONSTRATE THE ELECTRICAL SYSTEMS TO OWNER AND/OR OWNER'S REPRESENTATIVE.



| REVISIONS |      |             |
|-----------|------|-------------|
| No.       | Date | Description |
|           |      |             |
|           |      |             |
|           |      |             |
|           |      |             |
|           |      |             |
|           |      |             |
|           |      |             |
|           |      |             |
|           |      |             |
|           |      |             |

Information contained on this drawing and in all digital files associated is authorized for use on the project named herein only and is the property of MISHRA ARCHITECTURE PLLC and may not be reproduced in any manner without express written or verbal permission from authorized individuals. Original drawing is 24"x36" and scales are as indicated. 2011 MISHRA ARCHITECTURE PLLC



KEY PLAN

Pramukh Vicksburg, LLC

HOME2suites Vicksburg

Berryman Road Vicksburg, MS 39180

Drawing Title  
ELECTRICAL - COMMUNICATIONS RISERS & DETAILS

Phase  
Construction Documents

|             |          |           |      |
|-------------|----------|-----------|------|
| Project No. | 19005    | Sheet No. | E407 |
| Prepared by | PTH      |           |      |
| Checked by  | RJH      |           |      |
| Date        | 04/02/19 |           |      |

Released for



