

2 regular

DOOR SCHEDULE									
NO.	SIZE	DESCRIPTION							
T1	2'0" x 6'8"	D	H	J	L	R	Y	AA	
T2	2'0" x 6'8"	D	H	K	Q	V			
T3	2'0" x 6'8"	D	H	K	M	Q		BB	
1	6'0" x 7'0"	A	G	3/4"	W	R	Y	CC	
2	4'0" x 7'0"	A	G	3/4"	Y	Z	CC		
3	3'0" x 6'8"	D	H	K	Q	S			
4									
5	3'0" x 6'8"	D	H	J	L	R	S	Y	
6	3'0" x 6'8"	D	H	K	L	Q	S	Y	
7	3'0" x 6'8"	D	H	K	Q	S			
8	3'0" x 6'8"	D	H	K	Q	U			
9	3'0" x 6'8"	D	H	K	Q	U			
10	3'0" x 6'8"	D	H	K	M	Q	S	Y	
11	3'0" x 6'8"	D	H	K	Q	V			
12	2'0" x 6'8"	D	H	K	Q	U			
13	3'0" x 6'8"	D	H	K	Q	U			
14	3'0" x 6'8"	B	H		Q	S			
15	3'0" x 6'8"	B	H		P	Q	S		
16	3'0" x 7'0"	A	G	3/4"	W	R	Y	CC	
17	3'0" x 6'8"	D	H	J	M	R	S	Y	
18	3'0" x 6'8"	D	H	J	M	R	S	Y	
19	3'0" x 6'8"	D	H	J	R	V			
20	2'0" x 6'8"	D	H	K	Q	U			

DOOR SCHEDULE									
NO.	SIZE	DESCRIPTION							
21	2'0" x 6'8"	D	H	K	Q	S	Y		
22	3'0" x 6'8"	D	H	K	Q	S			
23	4'0" x 6'8"	D	H	J	M	R	S	Y	
24	3'0" x 6'8"	D	H	J	M	R	S	Y	
25	3'0" x 6'8"	F	H	J	N	R	U	Y	
26	3'0" x 7'0"	A	G	3/4"	W	R	Y	CC	
27	3'0" x 6'8"	D	H		Q	S			
28	3'0" x 6'8"	D	H		Q	S			
29	3'0" x 6'8"	D	H		M	Q	S	Y	

DOOR DESCR. LEGEND									
A	ALUM. ENTRANCE								
B	HOL. MET., FLUSH								
C	WOOD SOLID CORE								
D	MINERAL CORE								
E	ALUMINUM								
F	HOLLOW METAL								
G	POCKET DOOR								
H	BIRCH								
I	1/2" HARDBOARD								
J	20 MINUTE								
K	C = 3/4 HR.								
L	B = 1 HR.								
M	DOOR. HALF								
N	P FULL								
O	PAINT								
P	STAIN								
Q	KEYED LOCK								
R	EXT. DEVICE								
S	PASSAGE LATCH								
T	PRIVATE BATH LOCK								
U	W/STRIP GASKET								
V	ALUM. SADDLE								
W	CLOSING DEVICE								
X	ELEG. OPERATED LOCK								

DOOR DESCRIPTION LEGEND									
AA	HARDWARE:								
	MORTISE LOCK - ILCO SYSTEM								
	1 1/2" PR. SPRING HINGES (BOMMER)								
	SWING DOOR DOOR GUARD								
	ONE-WAY VIEWER (2 REQ'D @ HANDICAPPED; LOWER VIEWER 40" AFF.)								
	NOTES: LOCK/LEVER TO HAVE BRASS/ALUM. FINISH, VERIFY W/ OWNER.								
BB	HARDWARE:								
	SURFACE SLIDE BOLT								
	HINGES - 1 1/2" PR.								
CC	HARDWARE:								
	SOUNDSEAL - PENKO "SILICONE-SEAL" DOOR GASKET APPLIED TO FRAME HEAD & JAMB.								
	LATCHSET W/ OPERATING KNOB ROOM SIDE ONLY.								
	NOTE: PBL CARPET PAD UNDER DOOR FOR SNUG FIT TO RETARD SOUND TRANS.								
DD	KAMNEER OR EQUAL NARROW STILE (7/8" HG. POT. RAIL) W/ MFR'S STD. HARDWARE. SEE STOREFRONT ORDER FOR FINISH & GL.								
	NOTE: DOOR #2 TO HAVE MED. UTILE.								

FINISH SCHEDULE																								
NO.	ROOM	FLOOR					BASE					WALLS					CEILING					PAINT (GL. BKG.)	PAINT (GL. BKG.)	REMARKS
		CONCRETE	CARPET (600)	RESIL. TILE	CER. TILE (600)	CER. TILE (1200)	CARPET (4" (600))	VINYL	CERAMIC TILE	CER. TILE	CER. TILE	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)	CARPET (600)
1	VESTIBULE																							
2	LOBBY																							
3	SEATING																							
4	BRKFST./BUFFET																							
5	PANTRY																							
6	REGISTRATION																							
7	WORK																							
8	HALL																							
9	OFFICE																							
10	CORRIDOR																							
11	CORRIDOR																							
12	VENTING																							
13	PHONES																							
14	TOILET (PUBLIC)																							
15	STORAGE																							
16	UTILITY																							
17	LAUNDRY																							
18	CLEAN LINEN																							
19	GUEST LAUN.																							
20	STAIR																							
21	CORRIDOR																							
22	VENTING																							
23	STORAGE																							
24	LIN. WHITE RM.																							
25	STAIR																							
A	ENTRY																							
B	LIVING/DINING																							
C	BEDROOM																							
D	KITCHEN																							
E	DRESSING																							
T1	BEORM./LIVING																							
T2	ENTRY																							
T3	BATHRM																							

RICHARD MOLENAAR ARCHITECT

DAYS INN

PEARL, MS.

FINISH NOTES

- "Knock Down" (finish 13) to be "Plexure" as mfrd. by Triarch Industries, color and texture as selected. No substitute. Wall-paper border (BSP1) (color as mfrd. finish & texture).
- Susp. acct. pbl. clg. (finish 19) to be 24"x24"x5/8" lay-in panels, color and texture as selected, with reveal edge equal to "Armstrong" best grade humidity-resistant washable product.
- Susp. acct. pbl. clg. (finish 20) to be 24"x24"x5/8" lay-in panels, color and texture as selected, with reveal edge equal to "Armstrong" best grade humidity-resistant washable product.
- Grid for susp. acct. panel clgs. equal to "Donn" humidity resistant system.
- Provide 2"x2"x36" opaque plastic corner guards at all external corners of gyp. board walls in public areas and corridors. Verify style with Owner. In addition provide stained birch chair rail @ 36" above flr.
- Allow \$3,000 for door numbers and all interior signage.

- DOOR NOTES
- WOOD DOORS, HOLLOW METAL DOORS TO BE 3/4" THK. UNLESS NOTED OTHERWISE.
 - EXT. HOLLOW MET. DOORS TO OR FROM CONDITIONED SPACE TO BE INSULATED.
 - WHERE REQ'D, DOOR HARDWARE SHALL CONFORM TO ADA & GOVERNING HANDICAP CODE. ALL HOL. MET. & WOOD DOORS TO HAVE LEVER KNOBS.
 - WOOD & HOL. MET. DOORS THAT OPEN AGAINST A WALL TO HAVE BUMPER MOUNTED ON WALL WHEREVER POSSIBLE.
 - PROVIDE "ILCO" ELECTRONIC LOCK SYS-TEM @ DOORS #2, #10, #26 @ STAIR#, #27 FOR GUEST CARD ENTRY.
 - PROVIDE KICK PLATE ON PUSH SIDE OF DOOR 23 TO LAUNDRY.
 - PROVIDE 12"x12" WIRE GLASS VIEW LITE IN DOOR #27 @ GUEST LAUNDRY.
 - HOLLOW MET. DOOR FRAMES TO BE WELDED, EXCEPT "T2" DOOR FRAMES MAY BE "KNOCK-DOWN" TYPE.

WALL SCHEDULE									
NO.	DESCRIPTION	1	2	3	4	5	6	7	8
W1	EXT. CONC. BLK.								
W2	EXT. INS. FINISH SYS.								
W3	1/2" GYP. BD., MIN.								
W4	1/2" TYPE X GYP. BD.								
W5	1/2" RESIL. FURR. CHANNELS @ 16" OC.								
W6	1/2" TYPE X GYP. BD.								
W7	1/2" EXT. GYP. BD. SHEATHING								
W8	2"x4" W.D. STUDS @ 16" OC.								
W9	2"x6" W.D. STUDS @ 16" OC.								
W10	1" GYP. CORE DD.								

- WALL KEYNOTES
- 3" CONC. BLK.
 - EXT. INS. FINISH SYS.
 - 1/2" GYP. BD., MIN.
 - 1/2" TYPE X GYP. BD.
 - 1/2" RESIL. FURR. CHANNELS @ 16" OC.
 - 1/2" TYPE X GYP. BD.
 - 1/2" EXT. GYP. BD. SHEATHING
 - 2"x4" W.D. STUDS @ 16" OC.
 - 2"x6" W.D. STUDS @ 16" OC.
 - 1" GYP. CORE DD.

NOTE: FILL OPEN CELLS OF EXT. CONC. BLK. WALLS W/ "STYROFOAM" MGRY. FILL INSULATION.

